



## S20 BLACK Real 1-Step Compound

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

S20 BLACK Real 1-Step Compound

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Automotive care products

#### 1.3. Details of the supplier of the safety data sheet

Company name:	SCHOLL Concepts GmbH	
	Polish & Pad Manufaktur	
Street:	Maybachstrasse 7	
Place:	D-71686 Remseck	
Telephone:	+49 (0) 7141 29299 - 0	Telefax: +49 (0) 7141 29299 - 10
e-mail:	sds@schollconcepts.com	
Internet:	www.schollconcepts.com	

**1.4. Emergency telephone number:** +49 (0) 89 19240 (Giftnotruf Technische Universität München)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Regulation (EG) Nr. 1272/2008

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

#### 2.2. Label elements

##### Regulation (EG) Nr. 1272/2008

##### Hazard components for labelling

This product has been treated with biocides for preservation.

##### Precautionary statements

P102 Keep out of reach of children.

##### Special labelling of certain mixtures

EUH208	Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1). May produce an allergic reaction.
EUH210	Safety data sheet available on request.

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

**S20 BLACK Real 1-Step Compound****3.2. Mixtures****Hazardous components**

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (Regulation (EG) Nr. 1272/2008)			
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics			10 - < 15 %
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304 EUH066			
8042-47-5	white mineral oil ( petroleum )			1 - < 5 %
	232-455-8		01-2119487078-27	
	Asp. Tox. 1; H304			
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1)			< 0.1 %
	611-341-5	613-167-00-5		
	Acute Tox. 2, Acute Tox. 2, Acute Tox. 3, Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H310 H301 H314 H318 H317 H400 H410 EUH071			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. Limits, M-factors and ATE			
	918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	10 - < 15 %	
	dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg			
8042-47-5	232-455-8	white mineral oil ( petroleum )	1 - < 5 %	
	dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg			
55965-84-9	611-341-5	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1)	< 0.1 %	
	inhalation: ATE = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: LD50 = >141 mg/kg; oral: LD50 = 66 mg/kg Skin Corr. 1C; H314: >= 0,6 - 100 Skin Irrit. 2; H315: >= 0,06 - < 0,6 Eye Dam. 1; H318: >= 0,6 - 100 Eye Irrit. 2; H319: >= 0,06 - < 0,6 Skin Sens. 1A; H317: >= 0,0015 - 100 M acute; H400: M=100 M chron.; H410: M=100			

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

No special measures are necessary. When in doubt or if symptoms are observed, get medical advice.



## S20 BLACK Real 1-Step Compound

### After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off contaminated clothing and wash it before reuse.

### After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

### After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Foam. Dry extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Water spray jet. Co-ordinate fire-fighting measures to the fire surroundings.

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

No special measures are necessary.

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

#### For non-emergency personnel

Ventilate affected area. Wear personal protection equipment (refer to section 8). Do not breathe mist/vapours/spray.



## S20 BLACK Real 1-Step Compound

### For emergency responders

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

### 6.3. Methods and material for containment and cleaning up

#### For containment

Collect spillage.

#### For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

No special measures are necessary. Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

#### Advice on protection against fire and explosion

No special fire protection measures are necessary. Only use the material in places where open light, fire and other flammable sources can be kept away.

#### Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not smoke. When using do not eat or drink. Avoid contact with skin, eyes and clothes. Avoid breathing dust/fume/gas/mist/vapours/spray.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed.

#### Hints on joint storage

Oxidising agent. Strong acid. Strong alkali. Pyrophoric or self-heating substances

#### Further information on storage conditions

Recommended storage temperature: 15-25°C



## S20 BLACK Real 1-Step Compound

### 7.3. Specific end use(s)

Automotive care products

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
1344-28-1	Aluminium oxides, respirable dust	-	4		TWA (8 h)	WEL
56-81-5	Glycerol, mist	-	10		TWA (8 h)	WEL

#### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
1344-28-1	Aluminium oxide			
Worker DNEL, long-term		inhalation	local	15,63 mg/m <sup>3</sup>
Consumer DNEL, long-term		oral	systemic	3,29 mg/kg bw/day
8042-47-5	white mineral oil ( petroleum )			
Consumer DNEL, long-term		inhalation	systemic	35 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	93 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	160 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	220 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	40 mg/kg bw/day
1344-28-1	aluminium oxide			
Worker DNEL, long-term		inhalation	local	15,6 mg/m <sup>3</sup>
Consumer DNEL, long-term		oral	systemic	6,2 mg/kg bw/day
56-81-5	glycerol			
Worker DNEL, long-term		inhalation	local	220 mg/m <sup>3</sup>

## S20 BLACK Real 1-Step Compound

### PNEC values

CAS No	Substance	
Environmental compartment		Value
1344-28-1	Aluminium oxide	
Freshwater		0,0749 mg/l
Micro-organisms in sewage treatment plants (STP)		20 mg/l
1344-28-1	aluminium oxide	
Freshwater		0,0749 mg/l
Micro-organisms in sewage treatment plants (STP)		20 mg/l
56-81-5	glycerol	
Micro-organisms in sewage treatment plants (STP)		1000 mg/l

### 8.2. Exposure controls



#### Appropriate engineering controls

Use only in well-ventilated areas.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Wear eye/face protection.

##### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves must be worn.

Recommended glove articles: HyFlex® Foam (EN 420, EN 388 (3131)).

##### Skin protection

Wear suitable protective clothing.

##### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

##### Environmental exposure controls

No special environmental measures are necessary. Do not allow uncontrolled discharge of product into the environment.

**S20 BLACK Real 1-Step Compound****SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	grey
Odour:	characteristic

**Changes in the physical state**

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	100 °C
Flash point:	>61 °C

**Flammability**

Solid/liquid:	not applicable
Gas:	not applicable

Lower explosion limits:	0,5 vol. %
Upper explosion limits:	7 vol. %
Auto-ignition temperature:	>200 °C

**Self-ignition temperature**

Solid:	not applicable
Gas:	not applicable

Decomposition temperature:	not determined
----------------------------	----------------

pH-Value (at 20 °C):	7,8
----------------------	-----

Viscosity / dynamic: (at 20 °C)	20000-25000 mPa·s
------------------------------------	-------------------

Water solubility:	completely miscible
-------------------	---------------------

**Solubility in other solvents**

not determined

Partition coefficient n-octanol/water:	not determined
--	----------------

Vapour pressure: (at 20 °C)	0,6 hPa
--------------------------------	---------

Density (at 20 °C):	1,06 g/cm <sup>3</sup>
---------------------	------------------------

**9.2. Other information****Information with regard to physical hazard classes**

Oxidizing properties  
Not oxidising.



## S20 BLACK Real 1-Step Compound

### Other safety characteristics

Solvent content:	25,72 %
Solid content:	not determined
Evaporation rate:	not determined

### Further Information

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

### 10.4. Conditions to avoid

Only use the material in places where open light, fire and other flammable sources can be kept away.

### 10.5. Incompatible materials

Oxidising agent. Strong acid. Strong alkali.

### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in CLP Regulation

#### Toxicokinetics, metabolism and distribution

No information available.

#### Acute toxicity

Based on available data, the classification criteria are not met.



**S20 BLACK Real 1-Step Compound**

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics				
	oral	LD50 >5000 mg/kg	Rat	ECHA	OECD TG 401
	dermal	LD50 >5000 mg/kg	Rabbit	ECHA	OECD TG 402
8042-47-5	white mineral oil ( petroleum )				
	oral	LD50 >5000 mg/kg	Rat	ECHA	OECD 401
	dermal	LD50 >2000 mg/kg	Rabbit	ECHA	OECD 402
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1)				
	oral	LD50 66 mg/kg	Rat	Thor	
	dermal	LD50 >141 mg/kg		Thor	
	inhalation vapour	ATE 0,5 mg/l			
	inhalation dust/mist	ATE 0,05 mg/l			

**Irritation and corrosivity**

Based on available data, the classification criteria are not met.

**Sensitising effects**

Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1). May produce an allergic reaction.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Specific effects in experiment on an animal**

No information available.

**Additional information on tests**

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

## S20 BLACK Real 1-Step Compound

### SECTION 12: Ecological information

#### 12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics					
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	ECHA	OECD 203
	Acute algae toxicity	ErC50 >1000 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h	Daphnia magna (Big water flea)	ECHA	OECD 202
8042-47-5	white mineral oil ( petroleum )					
	Acute fish toxicity	LL50 >1000 mg/l	96 h	Leuciscus idus (golden orfe)	ECHA	OECD 203
	Acute algae toxicity	ErC50 >100 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Acute crustacea toxicity	EL50 >100 mg/l	48 h	Daphnia magna (Big water flea)	ECHA	OECD 202
	Algae toxicity	NOEC >=100 mg/l	72 d	Pseudokirchneriella subcapitata	ECHA	OECD 201
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1)					
	Acute fish toxicity	LC50 0,22 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	Thor	OECD 203
	Acute algae toxicity	ErC50 0,048 mg/l	72 h	Pseudokirchneriella subcapitata	Thor	OECD 201
	Acute crustacea toxicity	EC50 0,1 mg/l	48 h	Daphnia magna (Big water flea)	Thor	OECD 202
	Fish toxicity	NOEC 0,098 mg/l	28 d	Oncorhynchus mykiss (Rainbow trout)	Thor	OECD 210
	Algae toxicity	NOEC 0,0012 mg/l	3 d	Pseudokirchneriella subcapitata	Thor	OECD 201
	Crustacea toxicity	NOEC 0,004 mg/l	21 d	Daphnia magna (Big water flea)	Thor	OECD 211
	Acute bacteria toxicity	(EC50 7,92 mg/l)	3 h	Activated sludge		OECD 209

#### 12.2. Persistence and degradability

**S20 BLACK Real 1-Step Compound**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

CAS No	Chemical name	Method	Value	d	Source
		Evaluation			
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics				
	OECD 301 F		80%	28	ECHA
	Readily biodegradable (according to OECD criteria).				
8042-47-5	white mineral oil ( petroleum )				
	OECD 301 F		31 %	28	ECHA
	Not readily biodegradable (according to OECD criteria)				
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1)				
	OECD 301 A		>70 %	28	Thor
	Readily biodegradable (according to OECD criteria).				
	OECD 301 D		>60%		Thor
	Readily biodegradable (according to OECD criteria).				

**12.3. Bioaccumulative potential**

The product has not been tested.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
8042-47-5	white mineral oil ( petroleum )	>4

**BCF**

CAS No	Chemical name	BCF	Species	Source
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1)	3,16		EPIWIN, S 1177

**12.4. Mobility in soil**

The product has not been tested.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.



## S20 BLACK Real 1-Step Compound

### 12.7. Other adverse effects

No information available.

### Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

#### Contaminated packaging

Non-contaminated packages may be recycled.

## SECTION 14: Transport information

### Land transport (ADR/RID)

- |                                   |  |
|-----------------------------------|--|
| 14.1. UN number or ID number:     | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name:    | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group:              | No dangerous good in sense of this transport regulation. |

### Inland waterways transport (ADN)

- |                                   |  |
|-----------------------------------|--|
| 14.1. UN number or ID number:     | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name:    | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group:              | No dangerous good in sense of this transport regulation. |

### Marine transport (IMDG)

- |                                   |  |
|-----------------------------------|--|
| 14.1. UN number or ID number:     | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name:    | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group:              | No dangerous good in sense of this transport regulation. |

### Air transport (ICAO-TI/IATA-DGR)

- |                                   |  |
|-----------------------------------|--|
| 14.1. UN number or ID number:     | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name:    | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group:              | No dangerous good in sense of this transport regulation. |

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

**S20 BLACK Real 1-Step Compound****14.6. Special precautions for user**

No special measures are necessary.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 75

2010/75/EU (VOC): 15,771 % (167,168 g/l)

2004/42/EC (VOC): 15,79 % (167,376 g/l)

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

**Additional information**

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

**National regulatory information**

Water hazard class (D): 1 - slightly hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**Substance/product listed in the following inventories**

EU / Schweiz	yes
Taiwan	yes
New Zealand	unknown
USA	yes
Canada	yes
Australia	yes
Japan	yes
China	yes
Korea	yes
Philippines	yes

**SECTION 16: Other information****Changes**



## S20 BLACK Real 1-Step Compound

This data sheet contains changes from the previous version in section(s): 7,9,15.

### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%

### Relevant H and EUH statements (number and full text)

H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.
EUH208	Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1). May produce an allergic reaction.
EUH210	Safety data sheet available on request.

### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



## S20 BLACK Real 1-Step Compound

### Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Formulation or re-packing	F	-	-	8a, 9	2	-	-	
2	Automotive care products, Industrial uses	IS	-	-	7, 10, 17	4	-	-	
3	Automotive care products, Professional uses	PW	-	-	10, 11, 17	8a	-	-	
4	Automotive care products, Consumer use	C	-	31	-	8a	-	-	

LCS: Life cycle stages

SU: Sectors of use

PC: Product categories

PROC: Process categories

ERC: Environmental release categories

AC: Article categories

TF: Technical functions

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

© by SCHOLL Concepts GmbH