



S2 BLACK Rubbing Compound

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

S2 BLACK Rubbing Compound

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Automotive care products

1.3. Details of the supplier of the safety data sheet

| | | |
|---------------|-------------------------|----------------------------------|
| Company name: | SCHOLL Concepts GmbH | |
| | Polish & Pad Manufaktur | |
| Street: | Maybachstrasse 7 | |
| Place: | D-71686 Remseck | |
| Telephone: | +49 (0) 7141 29299 - 0 | Telefax: +49 (0) 7141 29299 - 10 |
| e-mail: | sds@schollconcepts.com | |
| Internet: | www.schollconcepts.com | |

1.4. Emergency telephone number: +49 (0) 89 19240 (Giftnotruf Technische Universität München)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EG) Nr. 1272/2008

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

2.2. Label elements

Regulation (EG) Nr. 1272/2008

Hazard components for labelling

This product has been treated with biocides for preservation.

Precautionary statements

P102 Keep out of reach of children.

Special labelling of certain mixtures

EUH208 Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1). May produce an allergic reaction.

EUH210 Safety data sheet available on request.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

**S2 BLACK Rubbing Compound****3.2. Mixtures****Hazardous components**

| CAS No | Chemical name | Quantity | | |
|------------|--|--------------|------------------|------------|
| | EC No | Index No | REACH No | |
| | Classification (Regulation (EG) Nr. 1272/2008) | | | |
| | Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics | | | 5 - < 10 % |
| | 920-114-2 | | 01-2119459347-30 | |
| | Asp. Tox. 1; H304 EUH066 | | | |
| 8042-47-5 | white mineral oil (petroleum) | | | 1 - < 5 % |
| | 232-455-8 | | 01-2119487078-27 | |
| | Asp. Tox. 1; H304 | | | |
| 55965-84-9 | mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1) | | | < 0.1 % |
| | 611-341-5 | 613-167-00-5 | | |
| | Acute Tox. 2, Acute Tox. 2, Acute Tox. 3, Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H310 H301 H314 H318 H317 H400 H410 EUH071 | | | |

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity | |
|------------|--|---|------------|--|
| | Specific Conc. Limits, M-factors and ATE | | | |
| | 920-114-2 | Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics | 5 - < 10 % | |
| | dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg | | | |
| 8042-47-5 | 232-455-8 | white mineral oil (petroleum) | 1 - < 5 % | |
| | dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg | | | |
| 55965-84-9 | 611-341-5 | mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1) | < 0.1 % | |
| | inhalation: ATE = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: LD50 = >141 mg/kg; oral: LD50 = 66 mg/kg Skin Corr. 1C; H314: >= 0,6 - 100 Skin Irrit. 2; H315: >= 0,06 - < 0,6 Eye Dam. 1; H318: >= 0,6 - 100 Eye Irrit. 2; H319: >= 0,06 - < 0,6 Skin Sens. 1A; H317: >= 0,0015 - 100 M acute; H400: M=100 M chron.; H410: M=100 | | | |

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

No special measures are necessary. When in doubt or if symptoms are observed, get medical advice.



S2 BLACK Rubbing Compound

After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off contaminated clothing and wash it before reuse.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a doctor.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Dry extinguishing powder. Carbon dioxide (CO₂). Water spray jet. Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Gases/vapours, irritant.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

For non-emergency personnel

Ventilate affected area. Wear personal protection equipment (refer to section 8). Do not breathe mist/vapours/spray.



S2 BLACK Rubbing Compound

For emergency responders

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Collect spillage.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

No special measures are necessary. Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

Advice on protection against fire and explosion

No special fire protection measures are necessary. Only use the material in places where open light, fire and other flammable sources can be kept away.

Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not smoke. When using do not eat or drink. Avoid contact with skin, eyes and clothes. Avoid breathing dust/fume/gas/mist/vapours/spray.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed.

Hints on joint storage

Do not store together with: Oxidising agent. Strong acid. Strong alkali.

Further information on storage conditions

Recommended storage temperature: 15-25°C

7.3. Specific end use(s)

Automotive care products



S2 BLACK Rubbing Compound

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m ³ | fibres/ml | Category | Origin |
|-----------|-----------------------------------|-----|-------------------|-----------|-----------|--------|
| 1344-28-1 | Aluminium oxides, respirable dust | - | 4 | | TWA (8 h) | WEL |
| 56-81-5 | Glycerol, mist | - | 10 | | TWA (8 h) | WEL |

DNEL/DMEL values

| CAS No | Substance | Exposure route | Effect | Value |
|--------------------------|---------------------------------|----------------|----------|-------------------------|
| 1344-28-1 | aluminium oxide | | | |
| Consumer DNEL, long-term | | oral | systemic | 6,58 mg/kg bw/day |
| Worker DNEL, long-term | | inhalation | local | 15,63 mg/m ³ |
| Worker DNEL, long-term | | inhalation | systemic | 15,63 mg/m ³ |
| 8042-47-5 | white mineral oil (petroleum) | | | |
| Consumer DNEL, long-term | | inhalation | systemic | 35 mg/m ³ |
| Consumer DNEL, long-term | | dermal | systemic | 93 mg/kg bw/day |
| Worker DNEL, long-term | | inhalation | systemic | 160 mg/m ³ |
| Worker DNEL, long-term | | dermal | systemic | 220 mg/kg bw/day |
| Consumer DNEL, long-term | | oral | systemic | 40 mg/kg bw/day |
| 56-81-5 | glycerol | | | |
| Worker DNEL, long-term | | inhalation | local | 220 mg/m ³ |

PNEC values

| CAS No | Substance | Value |
|--|-----------------|-------------|
| Environmental compartment | | |
| 1344-28-1 | aluminium oxide | |
| Freshwater | | 0,0749 mg/l |
| Micro-organisms in sewage treatment plants (STP) | | 20 mg/l |
| 56-81-5 | glycerol | |
| Micro-organisms in sewage treatment plants (STP) | | 1000 mg/l |

8.2. Exposure controls



S2 BLACK Rubbing Compound



Appropriate engineering controls

Use only in well-ventilated areas.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves must be worn.

Recommended glove articles: HyFlex® Foam (EN 420, EN 388 (3131)).

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

No special environmental measures are necessary. Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|-----------------|----------------|
| Physical state: | Liquid |
| Colour: | white |
| Odour: | characteristic |

Changes in the physical state

| | |
|---|----------------|
| Melting point/freezing point: | not determined |
| Boiling point or initial boiling point and boiling range: | 100 °C |
| Flash point: | 130 °C |

Flammability

| | |
|---------------|----------------|
| Solid/liquid: | not determined |
| Gas: | not applicable |



S2 BLACK Rubbing Compound

| | |
|--|------------------------|
| Auto-ignition temperature: | >200 °C |
| Self-ignition temperature | |
| Solid: | not determined |
| Gas: | not applicable |
| Decomposition temperature: | not determined |
| pH-Value (at 20 °C): | 7,8 |
| Viscosity / dynamic: (at 20 °C) | 12000-18000 mPa·s |
| Water solubility: (at 20 °C) | completely miscible |
| Solubility in other solvents | |
| not determined | |
| Partition coefficient n-octanol/water: | not determined |
| Vapour pressure: (at 20 °C) | <0,1 hPa |
| Density (at 20 °C): | 1,04 g/cm ³ |
| Relative vapour density: | not determined |

9.2. Other information

Information with regard to physical hazard classes

Oxidizing properties
Not oxidising.

Other safety characteristics

| | |
|-------------------|----------------|
| Solvent content: | 23,99 % |
| Solid content: | not determined |
| Evaporation rate: | not determined |

Further Information

Not sustaining combustion.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

**S2 BLACK Rubbing Compound****10.4. Conditions to avoid**

Only use the material in places where open light, fire and other flammable sources can be kept away.

10.5. Incompatible materials

Oxidising agent. Strong acid. Strong alkali.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in CLP Regulation****Toxicokinetics, metabolism and distribution**

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

| CAS No | Chemical name | | | | |
|------------|---|------------------|---------|--------|----------|
| | Exposure route | Dose | Species | Source | Method |
| | Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics | | | | |
| | oral | LD50 >5000 mg/kg | Rat | ECHA | OECD 401 |
| | dermal | LD50 >2000 mg/kg | Rabbit | ECHA | OECD 402 |
| 8042-47-5 | white mineral oil (petroleum) | | | | |
| | oral | LD50 >5000 mg/kg | Rat | ECHA | OECD 401 |
| | dermal | LD50 >2000 mg/kg | Rabbit | ECHA | OECD 402 |
| 55965-84-9 | mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1) | | | | |
| | oral | LD50 66 mg/kg | Rat | Thor | |
| | dermal | LD50 >141 mg/kg | | Thor | |
| | inhalation vapour | ATE 0,5 mg/l | | | |
| | inhalation dust/mist | ATE 0,05 mg/l | | | |

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects



S2 BLACK Rubbing Compound

Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1). May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

S2 BLACK Rubbing Compound

| CAS No | Chemical name | | | | | |
|------------|---|------------------|-----------|-------------------------------------|--------|----------|
| | Aquatic toxicity | Dose | [h] [d] | Species | Source | Method |
| | Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics | | | | | |
| | Acute fish toxicity | LC50 >1028 mg/l | 96 h | Scophthalmus maximus | ECHA | OECD 203 |
| | Acute algae toxicity | ErC50 >1000 mg/l | 72 h | Pseudokirchneriella subcapitata | ECHA | OECD 201 |
| | Acute crustacea toxicity | EL50 >1000 mg/l | 48 h | Ceriodaphnia spec | ECHA | OECD 202 |
| 8042-47-5 | white mineral oil (petroleum) | | | | | |
| | Acute fish toxicity | LL50 >1000 mg/l | 96 h | Leuciscus idus (golden orfe) | ECHA | OECD 203 |
| | Acute algae toxicity | ErC50 >100 mg/l | 72 h | Pseudokirchneriella subcapitata | ECHA | OECD 201 |
| | Acute crustacea toxicity | EL50 >100 mg/l | 48 h | Daphnia magna (Big water flea) | ECHA | OECD 202 |
| | Algae toxicity | NOEC >=100 mg/l | 72 d | Pseudokirchneriella subcapitata | ECHA | OECD 201 |
| 55965-84-9 | mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1) | | | | | |
| | Acute fish toxicity | LC50 0,22 mg/l | 96 h | Oncorhynchus mykiss (Rainbow trout) | Thor | OECD 203 |
| | Acute algae toxicity | ErC50 0,048 mg/l | 72 h | Pseudokirchneriella subcapitata | Thor | OECD 201 |
| | Acute crustacea toxicity | EC50 0,1 mg/l | 48 h | Daphnia magna (Big water flea) | Thor | OECD 202 |
| | Fish toxicity | NOEC 0,098 mg/l | 28 d | Oncorhynchus mykiss (Rainbow trout) | Thor | OECD 210 |
| | Algae toxicity | NOEC 0,0012 mg/l | 3 d | Pseudokirchneriella subcapitata | Thor | OECD 201 |
| | Crustacea toxicity | NOEC 0,004 mg/l | 21 d | Daphnia magna (Big water flea) | Thor | OECD 211 |
| | Acute bacteria toxicity | (EC50 7,92 mg/l) | 3 h | Activated sludge | | OECD 209 |

12.2. Persistence and degradability

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**S2 BLACK Rubbing Compound**

| CAS No | Chemical name | | | |
|------------|---|-------|----|--------|
| | Method | Value | d | Source |
| | Evaluation | | | |
| | Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics | | | |
| | OECD 306 | 74% | 28 | ECHA |
| | Readily biodegradable (according to OECD criteria). | | | |
| 8042-47-5 | white mineral oil (petroleum) | | | |
| | OECD 301F | 31 % | 28 | ECHA |
| | Not readily biodegradable (according to OECD criteria) | | | |
| 55965-84-9 | mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1) | | | |
| | OECD 301 A | >70 % | 28 | Thor |
| | Readily biodegradable (according to OECD criteria). | | | |
| | OECD 301 D | >60% | | Thor |
| | Readily biodegradable (according to OECD criteria). | | | |

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|-----------|---------------------------------|---------|
| 8042-47-5 | white mineral oil (petroleum) | >4 |

BCF

| CAS No | Chemical name | BCF | Species | Source |
|------------|---|------|---------|----------------|
| 55965-84-9 | mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1) | 3,16 | | EPIWIN, S 1177 |

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.



S2 BLACK Rubbing Compound

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

| | |
|-----------------------------------|--|
| 14.1. UN number or ID number: | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

Inland waterways transport (ADN)

| | |
|-----------------------------------|--|
| 14.1. UN number or ID number: | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

Marine transport (IMDG)

| | |
|-----------------------------------|--|
| 14.1. UN number or ID number: | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

Air transport (ICAO-TI/IATA-DGR)

| | |
|-----------------------------------|--|
| 14.1. UN number or ID number: | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments



S2 BLACK Rubbing Compound

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 75

2010/75/EU (VOC): 0 % (0 g/l)

2004/42/EC (VOC): 0 % (0,002 g/l)

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

Substance/product listed in the following inventories

| | |
|--------------|---------|
| EU / Schweiz | yes |
| Taiwan | yes |
| New Zealand | unknown |
| USA | yes |
| Canada | yes |
| Australia | yes |
| Japan | unknown |
| China | yes |
| Korea | yes |
| Philippines | yes |

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 6,7,9.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route



S2 BLACK Rubbing Compound

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

| | |
|--------|---|
| H301 | Toxic if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H310 | Fatal in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H330 | Fatal if inhaled. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
| EUH071 | Corrosive to the respiratory tract. |
| EUH208 | Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1). May produce an allergic reaction. |
| EUH210 | Safety data sheet available on request. |

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



S2 BLACK Rubbing Compound

Identified uses

| No | Short title | LCS | SU | PC | PROC | ERC | AC | TF | Specification |
|----|--|-----|----|----|------------|-----|----|----|---------------|
| 1 | Formulation or re-packing | F | - | - | 8a, 9 | 2 | - | - | |
| 2 | Automotive care products, Industrial uses | IS | - | - | 7, 10, 17 | 4 | - | - | |
| 3 | Automotive care products, Professional uses | PW | - | - | 10, 11, 17 | 8a | - | - | |
| 4 | Automotive care products, Consumer use | C | - | 31 | - | 8a | - | - | |

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

© by SCHOLL Concepts GmbH