RAPID Plus Engine & Chassis Cleaner

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

RAPID Plus Engine & Chassis Cleaner

UFI: GNRQ-E1RY-1UDV-8ED1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Washing and cleaning products

1.3. Details of the supplier of the safety data sheet

Company name: SCHOLL Concepts GmbH
Polish & Pad Manufaktur
Street: Maybachstrasse 7
Place: D-71686 Remseck
Telephone: +49 (0) 7141 29299 - 0 Telefax: +49 (0) 7141 29299 - 10
E-mail: sds@schollconcepts.com
Contact person: Labor
Internet: www.schollconcepts.com

1.4. Emergency telephone number: +49 (0) 89 19240 (Giftnotruf Technische Universität München)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) Nr. 1272/2008

Skin Corr. 1B; H314
Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) Nr. 1272/2008

Hazard components for labelling

tetrasodium ethylene diamine tetraacetate
Octyldecyl Glucoside
Cocamidopropyl betaine
disodium metasilicate pentahydrate

Signal word: Danger

RAPID Plus Engine & Chassis Cleaner

Pictograms:



Hazard statements

H314	Causes severe skin burns and eye damage.

Precautionary statements

P102	Keep out of reach of children.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P315	Get immediate medical advice/attention.
P501	Dispose of waste according to applicable legislation.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

RAPID Plus Engine & Chassis Cleaner

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) Nr. 1272/2008)			
64-02-8	tetrasodium ethylene diamine tetraacetate			5 - < 10 %
	200-573-9	607-428-00-2	01-2119486762-27	
	Acute Tox. 4, Eye Dam. 1; H302 H318			
1310-73-2	Sodium hydroxide			2 - < 5 %
	215-185-5		01-2119457892-27	
	Met. Corr. 1, Skin Corr. 1A; H290 H314			
68515-73-1	Octyldecyl Glucoside			1 - < 5 %
	500-220-1		01-2119488530-36	
	Eye Dam. 1; H318			
97862-59-4	Cocamidopropyl betaine			1 - < 5 %
	931-296-8		01-2119488533-30	
	Eye Dam. 1, Aquatic Chronic 3; H318 H412			
10213-79-3	disodium metasilicate pentahydrate			1 - < 5 %
	229-912-9	014-010-00-8	01-2119449811-37	
	Met. Corr. 1, Skin Corr. 1B, STOT SE 3; H290 H314 H335			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64-02-8	200-573-9	tetrasodium ethylene diamine tetraacetate	5 - < 10 %
	oral: LD50 = 1780-2000 mg/kg		
1310-73-2	215-185-5	Sodium hydroxide	2 - < 5 %
	dermal: LD50 = 1350 mg/kg; oral: LD50 = >191 mg/kg Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2		
68515-73-1	500-220-1	Octyldecyl Glucoside	1 - < 5 %
	dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg		
97862-59-4	931-296-8	Cocamidopropyl betaine	1 - < 5 %
	dermal: LD50 = >2000 mg/kg; oral: LD50 = 2335 mg/kg		
10213-79-3	229-912-9	disodium metasilicate pentahydrate	1 - < 5 %
	oral: LD50 = 1400 mg/kg		

Labelling for contents according to Regulation (EC) No 648/2004

5 % - < 15 % EDTA and salts thereof, < 5 % non-ionic surfactants, < 5 % amphoteric surfactants.

RAPID Plus Engine & Chassis Cleaner

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

IF exposed or concerned: Call a doctor. When in doubt or if symptoms are observed, get medical advice. Remove contaminated, saturated clothing immediately.

After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Dry extinguishing powder. Carbon dioxide (CO2). Water spray jet. Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Gases/vapours, corrosive

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

RAPID Plus Engine & Chassis Cleaner

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

For non-emergency personnel

Remove all sources of ignition.Remove persons to safety. Ventilate affected area. Wear personal protection equipment (refer to section 8).

For emergency responders

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Use personal protection equipment. Material, alkali-resistant

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

For containment

Stop leak if safe to do so. Cover drains. Collect spillage. Collect in closed and suitable containers for disposal.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Use non-sparking tools. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Handle and open container with care.

Advice on protection against fire and explosion

No special fire protection measures are necessary. Only use the material in places where open light, fire and other flammable sources can be kept away.

Advice on general occupational hygiene

Wear protective gloves/protective clothing. Remove contaminated, saturated clothing immediately. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. When using do not smoke. Avoid contact with skin, eyes and clothes. Avoid breathing

dust/fume/gas/mist/vapours/spray. Draw up and observe skin protection programme.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations.

Hints on joint storage

Do not store together with: Oxidising agent. Strong acid. Strong alkali.

Further information on storage conditions

Recommended storage temperature: 15-25°C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
1310-73-2	Sodium hydroxide	-	2		STEL (15 min)	WEL

RAPID Plus Engine & Chassis Cleaner

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64-02-8	tetrasodium ethylene diamine tetraacetate			
Worker DNEL, long-term		inhalation	local	1,5 mg/m³
Worker DNEL, acute		inhalation	local	3 mg/m³
Consumer DNEL, long-term		inhalation	local	0,6 mg/m³
Consumer DNEL, acute		inhalation	local	1,2 mg/m³
Consumer DNEL, long-term		oral	systemic	25 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	3 mg/m³
1310-73-2	Sodium hydroxide			
Worker DNEL, long-term		inhalation	local	1 mg/m³
Consumer DNEL, long-term		inhalation	local	1 mg/m³
68515-73-1	Octyldecyl Glucoside			
Worker DNEL, long-term		inhalation	systemic	420 mg/m³
Worker DNEL, long-term		dermal	systemic	595000 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	124 mg/m³
Consumer DNEL, long-term		dermal	systemic	357000 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	35,7 mg/kg bw/day
97862-59-4	Cocamidopropyl betaine			
Worker DNEL, long-term		inhalation	systemic	44 mg/m³
Worker DNEL, long-term		dermal	systemic	12,5 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	13,04 mg/m³
Consumer DMEL, long-term		dermal	systemic	7,5 mg/kg bw/day
10213-79-3	disodium metasilicate pentahydrate			
Worker DNEL, long-term		inhalation	systemic	6,22 mg/m³
Worker DNEL, long-term		dermal	systemic	1,49 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	1,55 mg/m³
Consumer DNEL, long-term		dermal	systemic	0,74 mg/kg bw/day

RAPID Plus Engine & Chassis Cleaner

Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day

PNEC values

CAS No	Substance
Environmental compartment	Value
64-02-8	tetrasodium ethylene diamine tetraacetate
Freshwater	2,83 mg/l
Marine water	0,283 mg/l
Micro-organisms in sewage treatment plants (STP)	50 mg/l
Soil	1,1 mg/kg
68515-73-1	Octyldecyl Glucoside
Freshwater	0,176 mg/l
Marine water	0,018 mg/l
Freshwater sediment	1,516 mg/kg
Marine sediment	0,152 mg/kg
Soil	0,654 mg/kg
97862-59-4	Cocamidopropyl betaine
Freshwater	0,013 mg/l
Marine water	0,001 mg/l
Freshwater sediment	11,1 mg/kg
Marine sediment	1,11 mg/kg
Soil	0,85 mg/kg
10213-79-3	disodium metasilicate pentahydrate
Freshwater	7,5 mg/l
Freshwater (intermittent releases)	7,5 mg/l
Marine water	1 mg/l

8.2. Exposure controls





Appropriate engineering controls

Use only in well-ventilated areas. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye protection/face protection. Suitable eye protection: Eye glasses with side protection (EN 166)

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.
Recommended glove articles : Dermatril P 743, Thickness of the glove material 0,2 mm, level 2 >= 30 min. (DIN EN 374)

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

No special environmental measures are necessary. Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	blue	
Odour:	characteristic	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		100 °C
Flammability:		not applicable
		not applicable
Lower explosion limits:		not applicable
Upper explosion limits:		not applicable
Flash point:		not applicable
Auto-ignition temperature:		not applicable
Decomposition temperature:		not determined
pH-Value (at 20 °C):		10,9
Water solubility:		easily soluble

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined

Vapour pressure: (at 20 °C)	not applicable
Vapour pressure: (at 50 °C)	not applicable
Relative density (at 20 °C):	1,085
Relative vapour density:	not determined

9.2. Other information

Information with regard to physical hazard classes

Oxidizing properties

Not oxidising.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Frost

10.5. Incompatible materials

Strong acid. Strong alkali. Oxidising agent.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in CLP Regulation

Toxicocinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 5000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

RAPID Plus Engine & Chassis Cleaner

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-02-8	tetrasodium ethylene diamine tetraacetate				
	oral	LD50 1780-2000 mg/kg	Rat	ECHA	OECD 401
1310-73-2	Sodium hydroxide				
	oral	LD50 >191 mg/kg	Rat		
	dermal	LD50 1350 mg/kg	Rabbit		
68515-73-1	Octyldecyl Glucoside				
	oral	LD50 >2000 mg/kg	Rat	ECHA	
	dermal	LD50 >2000 mg/kg	Rabbit	ECHA	OECD 402
97862-59-4	Cocamidopropyl betaine				
	oral	LD50 2335 mg/kg	Rat	ECHA	OECD 401
	dermal	LD50 >2000 mg/kg	Rat	ECHA	OECD 402
10213-79-3	disodium metasilicate pentahydrate				
	oral	LD50 1400 mg/kg	Rat		

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.
Serious eye damage/eye irritation: Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.
Carcinogenicity: Based on available data, the classification criteria are not met.
Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] | [d]	Species	Source	Method
64-02-8	tetrasodium ethylene diamine tetraacetate						
	Acute fish toxicity	LC50 mg/l	>100	96 h	Oncorhynchus mykiss (Rainbow trout)	ECHA	OECD 203
	Acute algae toxicity	ErC50 mg/l	>100	72 h	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Acute crustacea toxicity	EC50 mg/l	>100	48 h	Daphnia magna (Big water flea)	ECHA	DIN 38412, part 11
	Fish toxicity	NOEC mg/l	>35,1	35 d	Danio rerio (zebrafish)	ECHA	OECD 210
	Algae toxicity	NOEC mg/l	48,4	3 d	Pseudokirchneriella subcapitata	ECHA	OECD 201
1310-73-2	Sodium hydroxide						
	Acute fish toxicity	LC50 mg/l	45,4	96 h	Onchorhynchus mykiss		
	Acute crustacea toxicity	EC50 mg/l	30-100	48 h	Saltwater Shrimp	ECHA	
68515-73-1	Octyldecyl Glucoside						
	Acute fish toxicity	LC50 mg/l	100,81	96 h	Danio rerio (zebrafish)	ECHA	ISO 7346/1-3
	Acute algae toxicity	ErC50 mg/l	27,22	72 h	Scenedesmus subspicatus	ECHA	DIN 38412, part 9
	Acute crustacea toxicity	EC50 mg/l	>100	48 h	Daphnia magna (Big water flea)	ECHA	OECD 202
10213-79-3	disodium metasilicate pentahydrate						
	Acute fish toxicity	LC50 mg/l	3185	96 h	Danio rerio (zebrafish)		
	Acute algae toxicity	ErC50	207 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA	
	Acute crustacea toxicity	EC50 mg/l	4857	48 h	Daphnia magna (Big water flea)		

12.2. Persistence and degradability

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
The surfactants contained in this mixture comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64-02-8	tetrasodium ethylene diamine tetraacetate			
	OECD 301D	2%	28	ECHA
	Poorly biodegradable. Not readily biodegradable (according to OECD criteria)			
68515-73-1	Octyldecyl Glucoside			
	OECD Guideline 301 E	100%	28	ECHA
	Readily biodegradable (according to OECD criteria).			
97862-59-4	Cocamidopropyl betaine			
	ISO/DIS 14593	87,2%	28	ECHA
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.
The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

This material and its container must be disposed of as hazardous waste. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the

substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1719
14.2. UN proper shipping name:	CAUSTIC ALKALI LIQUID, N.O.S. (SODIUM HYDROXIDE, SOLID)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8



Classification code:	C5
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 1719
14.2. UN proper shipping name:	CAUSTIC ALKALI LIQUID, N.O.S. (SODIUM HYDROXIDE, SOLID)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8



Classification code:	C5
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1

Marine transport (IMDG)

14.1. UN number or ID number:	UN 1719
14.2. UN proper shipping name:	CAUSTIC ALKALI LIQUID, N.O.S. (SODIUM HYDROXIDE, SOLID)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8

RAPID Plus Engine & Chassis Cleaner



Special Provisions:	223, 274
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-A, S-B
Segregation group:	18 - alkalis

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 1719
14.2. UN proper shipping name:	CAUSTIC ALKALI LIQUID, N.O.S. (SODIUM HYDROXIDE, SOLID)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8



Special Provisions:	A3 A803	
Limited quantity Passenger:	1 L	
Passenger LQ:	Y841	
Excepted quantity:	E1	
IATA-packing instructions - Passenger:		852
IATA-max. quantity - Passenger:		5 L
IATA-packing instructions - Cargo:		856
IATA-max. quantity - Cargo:		60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Directive 2010/75/EU on industrial emissions:	0%
Directive 2004/42/EC on VOC in paints and varnishes:	0%

RAPID Plus Engine & Chassis Cleaner

Information according to Directive 2012/18/EU (SEVESO III):	Not subject to 2012/18/EU (SEVESO III)

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC
Regulation (EC) No. 648/2004 [Detergents regulation]

National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D):	3 - highly hazardous to water

Substance/product listed in the following inventories

EU / Schweiz	yes
Taiwan	unknown
New Zealand	yes
USA	yes
Canada	unknown
Australia	yes
Japan	yes
China	unknown
Korea	no
Philippines	yes

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,11,14.

RAPID Plus Engine & Chassis Cleaner

Abbreviations and acronyms

Met. Corr. 1: Corrosive to metals, hazard category 1
Acute Tox. 4: Acute toxicity, hazard category 4
Skin Corr. 1A: Skin corrosion, sub-category 1A
Eye Dam. 1: Serious eye damage, hazard category 1
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method

Relevant H and EUH statements (number and full text)

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

© by SCHOLL Concepts GmbH