W6+ Premium Glaze Wax

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

W6+ Premium Glaze Wax

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Automotive care products

1.3. Details of the supplier of the safety data sheet

Company name:	SCHOLL Concepts GmbH Polish & Pad Manufaktur	
Street:	Maybachstrasse 7	
Place:	D-71686 Remseck	
Telephone:	+49 (0) 7141 29299 - 0	Telefax: +49 (0) 7141 29299 - 10
E-mail:	sds@schollconcepts.com	
Internet:	www.schollconcepts.com	

1.4. Emergency telephone number: +49 (0) 89 19240 (Giftnotruf Technische Universität München)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) Nr. 1272/2008

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) Nr. 1272/2008

Hazard components for labelling

This product has been treated with biocides for preservation.

Hazard statements

H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P102	Keep out of reach of children.
P273	Avoid release to the environment.
P501	Dispose of waste according to applicable legislation.

Special labelling of certain mixtures

EUH205	Contains epoxy constituents. May produce an allergic reaction.
EUH208	Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and

2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1). May produce an allergic reaction.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) Nr. 1272/2008)			
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 0,1% Benzene			1 - < 5 %
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304 EUH066			
64742-49-0	hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes			1 - < 5 %
	927-510-4		01-2119475515-33	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411 EUH066			
64-17-5	ethanol			1 - < 5 %
	200-578-6			
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
67-63-0	isopropanol			1 - < 5 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
8042-47-5	white mineral oil (petroleum)			1 - < 5 %
	232-455-8		01-2119487078-27	
	Asp. Tox. 1; H304			
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1)			< 0.0015 %
	611-341-5	613-167-00-5		
	Acute Tox. 2, Acute Tox. 2, Acute Tox. 3, Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H310 H301 H314 H318 H317 H400 H410 EUH071			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64742-48-9	918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 0,1% Benzene	1 - < 5 %
	dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg		
64742-49-0	927-510-4	hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes	1 - < 5 %
	inhalation: LC50 = >23,3 mg/l (vapours); dermal: LD50 = >2920 mg/kg; oral: LD50 = >5840 mg/kg		
64-17-5	200-578-6	ethanol	1 - < 5 %
	inhalation: LC50 = 117-125 mg/l (vapours); dermal: LD50 = 17100 mg/kg; oral: LD50 = 10470 mg/kg Eye Irrit. 2; H319: >= 50 - 100		
67-63-0	200-661-7	isopropanol	1 - < 5 %
	dermal: LD50 = 12800 mg/kg; oral: LD50 = 5840 mg/kg		
8042-47-5	232-455-8	white mineral oil (petroleum)	1 - < 5 %
	inhalation: LC50 = >5 mg/l (dusts or mists); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg		
55965-84-9	611-341-5	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1)	< 0.0015 %
	inhalation: ATE = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: LD50 = >141 mg/kg; oral: LD50 = 66 mg/kg Skin Corr. 1C; H314: >= 0,6 - 100 Skin Irrit. 2; H315: >= 0,06 - < 0,6 Eye Dam. 1; H318: >= 0,6 - 100 Eye Irrit. 2; H319: >= 0,06 - < 0,6 Skin Sens. 1A; H317: >= 0,0015 - 100 Aquatic Acute 1; H400: M=100 Aquatic Chronic 1; H410: M=100		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No special measures are necessary. When in doubt or if symptoms are observed, get medical advice.

After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off contaminated clothing and wash it before reuse.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a doctor.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Dry extinguishing powder. Carbon dioxide (CO2). Water spray jet. Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

No special measures are necessary.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

For non-emergency personnel

Remove all sources of ignition. Ventilate affected area. Wear personal protection equipment (refer to section 8).

For emergency responders

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Use personal protection equipment. Tested protective gloves must be worn: Recommended material: NBR (Nitrile rubber). Unsuitable material: PVC (polyvinyl chloride)

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

For containment

Collect spillage. Stop leak if safe to do so. Cover drains.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Use non-sparking tools. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

No special measures are necessary. Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

Advice on protection against fire and explosion

No special fire protection measures are necessary. Only use the material in places where open light, fire and other flammable sources can be kept away.

Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not smoke. When using do not eat or drink. Avoid contact with skin, eyes and clothes. Avoid breathing dust/fume/gas/mist/vapours/spray.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed.

Hints on joint storage

Do not store together with: Oxidising agent. Strong acid. Strong alkali.

Further information on storage conditions

Recommended storage temperature: 15-25°C

7.3. Specific end use(s)

Automotive care products

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

W6+ Premium Glaze Wax

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
110-82-7	Cyclohexane	100	350		TWA (8 h)	WEL
		300	1050		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
1332-58-7	Kaolin respirable dust	-	2		TWA (8 h)	WEL
142-82-5	n-Heptane	500	2085		TWA (8 h)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

W6+ Premium Glaze Wax

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64742-49-0	hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes			
Consumer DNEL, long-term		dermal	systemic	149 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	2085 mg/m³
Consumer DNEL, long-term		inhalation	systemic	477 mg/m³
Consumer DNEL, long-term		oral	systemic	149 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	300 mg/kg bw/day
64-17-5	ethanol			
Consumer DNEL, long-term		oral	systemic	87 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	280 mg/m³
Worker DNEL, long-term		dermal	systemic	8238 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	114 mg/m³
67-63-0	isopropanol			
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	89 mg/m³
Worker DNEL, long-term		inhalation	systemic	500 mg/m³
8042-47-5	white mineral oil (petroleum)			
Consumer DNEL, long-term		inhalation	systemic	34,78 mg/m³
Consumer DNEL, long-term		dermal	systemic	93,02 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	164,56 mg/m³
Worker DNEL, long-term		dermal	systemic	217,05 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	25 mg/kg bw/day

W6+ Premium Glaze Wax

PNEC values

CAS No	Substance	
Environmental compartment		Value
64-17-5	ethanol	
Freshwater		0,96 mg/l
Marine water		0,79 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		2,9 mg/kg
Secondary poisoning		0,38 mg/kg
Micro-organisms in sewage treatment plants (STP)		580 mg/l
Soil		0,63 mg/kg

8.2. Exposure controls



Appropriate engineering controls

Use only in well-ventilated areas.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye protection/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.
Recommended glove articles : Rotiprotect Nitril eco , Thickness of the glove material 0,1 mm,
level 2 > 30 min. (DIN EN 374), Disposable gloves

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment. Do not allow to enter into soil/subsoil.

W6+ Premium Glaze Wax

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Paste
Colour:	red
Odour:	fruity

		Test method
Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	78 °C	
Flammability:	not applicable	
	not applicable	
Lower explosion limits:	2 vol. %	
Upper explosion limits:	12 vol. %	
Flash point:	36,5 °C	DIN 51755
Auto-ignition temperature:	>200 °C	
Decomposition temperature:	not determined	
pH-Value (at 20 °C):	7,1	
Viscosity / kinematic: (at 40 °C)	>20,5 mm²/s	
Water solubility: (at 20 °C)	completely miscible	
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:	not determined	
Vapour pressure: (at 20 °C)	48 hPa	
Density (at 20 °C):	0,96 g/cm³	
Relative vapour density:	not determined	

9.2. Other information

Information with regard to physical hazard classes

Sustained combustibility:	No sustained combustibility
Oxidizing properties	
Not oxidising.	

Other safety characteristics

Viscosity / dynamic: (at 20 °C)	8000-13000 mPa·s

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Only use the material in places where open light, fire and other flammable sources can be kept away.

10.5. Incompatible materials

Oxidising agent. Strong acid. Strong alkali.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in CLP Regulation

Toxicocinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

W6+ Premium Glaze Wax

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 0,1% Benzene				
	oral	LD50 >5000 mg/kg	Rat	ECHA	OECD TG 401
	dermal	LD50 >5000 mg/kg	Rabbit	ECHA	OECD TG 402
64742-49-0	hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes				
	oral	LD50 >5840 mg/kg	Rat	ECHA	OECD 401
	dermal	LD50 >2920 mg/kg	Rabbit	ECHA	OECD 402
	inhalation (4 h) vapour	LC50 >23,3 mg/l	Rat	ECHA	OECD 403
64-17-5	ethanol				
	oral	LD50 10470 mg/kg	Rat	ECHA	OECD 401
	dermal	LD50 17100 mg/kg	Rabbit	ECHA	
	inhalation (4 h) vapour	LC50 117-125 mg/l	Rat	ECHA	OECD 403
67-63-0	isopropanol				
	oral	LD50 5840 mg/kg	Rat	ECHA	OECD 401
	dermal	LD50 12800 mg/kg	Rabbit	GESTIS	
8042-47-5	white mineral oil (petroleum)				
	oral	LD50 >5000 mg/kg	Rat	ECHA	OECD 401
	dermal	LD50 >2000 mg/kg	Rabbit	ECHA	OECD 402
	inhalation (4 h) dust/mist	LC50 >5 mg/l	Rat		
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1)				
	oral	LD50 66 mg/kg	Rat	Thor	
	dermal	LD50 >141 mg/kg		Thor	
	inhalation vapour	ATE 0,5 mg/l			

W6+ Premium Glaze Wax

	inhalation dust/mist	ATE	0,05 mg/l			

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.
Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.
Contains epoxy constituents. May produce an allergic reaction.
Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1). May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.
Carcinogenicity: Based on available data, the classification criteria are not met.
Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

W6+ Premium Glaze Wax

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] | [d]	Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 0,1% Benzene						
	Acute fish toxicity	LC50 mg/l	>1000	96 h	Oncorhynchus mykiss (Rainbow trout)	ECHA	OECD 203
	Acute algae toxicity	ErC50 mg/l	>1000	72 h	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Acute crustacea toxicity	EC50 mg/l	>1000	48 h	Daphnia magna (Big water flea)	ECHA	OECD 202
64742-49-0	hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes						
	Acute fish toxicity	LL50 mg/l	13,4	96 h	Oncorhynchus mykiss (Rainbow trout)	ECHA	
	Acute algae toxicity	ErC50 mg/l	10-30	72 h	Pseudokirchneriella subcapitata	ECHA	
	Acute crustacea toxicity	EL50	3 mg/l	48 h	Daphnia magna (Big water flea)	ECHA	
64-17-5	ethanol						
	Acute fish toxicity	LC50 mg/l	11200	96 h	Salmo gairdneri	ECHA	US EPA method E03-05
	Acute algae toxicity	ErC50	275 mg/l	72 h	Chlorella vulgaris	ECHA	OECD 201
	Acute crustacea toxicity	EC50 mg/l	5012	48 h	Ceriodaphnia dubia	ECHA	ASTM E729-80
	Algae toxicity	NOEC	280 mg/l	7 d	Lemna gibba (swollen duckweed)	ECHA	
67-63-0	isopropanol						
	Acute fish toxicity	LC50 mg/l	9640	96 h	Pimephales promelas (fathead minnow)	ECHA	OECD 203
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 mg/l	9714	48 h	Daphnia magna (Big water flea)	ECHA	OECD 202
8042-47-5	white mineral oil (petroleum)						
	Acute fish toxicity	LL50 mg/l	>1000	96 h	Leuciscus idus (golden orfe)	ECHA	OECD 203
	Acute algae toxicity	ErC50 mg/l	>100	72 h	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Acute crustacea toxicity	EL50 mg/l	>100	48 h	Daphnia magna (Big water flea)	ECHA	OECD 202
	Algae toxicity	NOEC mg/l	>=100	72 d	Pseudokirchneriella subcapitata	ECHA	OECD 201

55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1)						
	Acute fish toxicity	LC50	0,22 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	Thor	OECD 203
	Acute algae toxicity	ErC50	0,048 mg/l	72 h	Pseudokirchneriella subcapitata	Thor	OECD 201
	Acute crustacea toxicity	EC50	0,1 mg/l	48 h	Daphnia magna (Big water flea)	Thor	OECD 202
	Fish toxicity	NOEC	0,098 mg/l	28 d	Oncorhynchus mykiss (Rainbow trout)	Thor	OECD 210
	Algae toxicity	NOEC	0,0012 mg/l	3 d	Pseudokirchneriella subcapitata	Thor	OECD 201
	Crustacea toxicity	NOEC	0,004 mg/l	21 d	Daphnia magna (Big water flea)	Thor	OECD 211
	Acute bacteria toxicity	EC50	7,92 mg/l ( )	3 h	Activated sludge		OECD 209

12.2. Persistence and degradability

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

W6+ Premium Glaze Wax

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 0,1% Benzene			
	OECD 301 F	80%	28	ECHA
	Readily biodegradable (according to OECD criteria).			
64742-49-0	hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes			
	OECD 301 F	98%	28	ECHA
	Readily biodegradable (according to OECD criteria).			
64-17-5	ethanol			
		84%	20	ECHA
	Readily biodegradable (according to OECD criteria).			
67-63-0	isopropanol			
	EU Method C.5	53%	5	ECHA
	Readily biodegradable (according to OECD criteria).			
8042-47-5	white mineral oil (petroleum)			
	OECD 301F	31 %	28	ECHA
	Not readily biodegradable (according to OECD criteria)			
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1)			
	OECD 301 A	>70 %	28	Thor
	Readily biodegradable (according to OECD criteria).			
	OECD 301 D	>60%		Thor
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol	-0,31
67-63-0	isopropanol	0,05
8042-47-5	white mineral oil (petroleum)	>4

BCF

CAS No	Chemical name	BCF	Species	Source
64-17-5	ethanol	3,2		ECHA
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1)	3,16		EPIWIN, S 1177

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.
The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 29, Entry 40, Entry 57, Entry 75

Directive 2010/75/EU on industrial emissions: 14,809 % (142,169 g/l)

Directive 2004/42/EC on VOC in paints and varnishes: 14,811 % (142,182 g/l)

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

Substance/product listed in the following inventories

EU / Schweiz	yes
Taiwan	unknown
New Zealand	unknown
USA	yes
Canada	yes
Australia	no
Japan	no
China	yes
Korea	no
Philippines	no

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 6,9,15.

Abbreviations and acronyms

Flam. Liq. 2: Flammable liquids, hazard category 2
Acute Tox. 2: Acute toxicity, hazard category 2
Asp. Tox. 1: Aspiration hazard, hazard category 1
Skin Corr. 1C: Skin corrosion, sub-category 1C
Skin Irrit. 2: Skin irritation, hazard category 2
Eye Dam. 1: Serious eye damage, hazard category 1
Eye Irrit. 2: Eye irritation, hazard category 2
Skin Sens. 1A: Skin sensitisation, hazard category 1A
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1
Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

W6+ Premium Glaze Wax

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.
EUH205	Contains epoxy constituents. May produce an allergic reaction.
EUH208	Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1). May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

W6+ Premium Glaze Wax

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Formulation or re-packing	F	-	-	8a, 9	2	-	-	
2	Automotive care products, Industrial uses	IS	-	-	7, 10, 17	4	-	-	
3	Automotive care products, Professional uses	PW	-	-	10, 11, 17	8a	-	-	
4	Automotive care products, Consumer use	C	-	31	-	8a	-	-	

LCS: Life cycle stages
SU: Sectors of use
PC: Product categories
PROC: Process categories
ERC: Environmental release categories
AC: Article categories
TF: Technical functions

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

© by SCHOLL Concepts GmbH