



W9 2 in 1 Premium Glaze Wax

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

W9 2 in 1 Premium Glaze Wax

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Automotive care products

1.3. Details of the supplier of the safety data sheet

Company name:	SCHOLL Concepts GmbH	
	Polish & Pad Manufaktur	
Street:	Maybachstrasse 7	
Place:	D-71686 Remseck	
Telephone:	+49 (0) 7141 29299 - 0	Telefax: +49 (0) 7141 29299 - 10
e-mail:	sds@schollconcepts.com	
Internet:	www.schollconcepts.com	

1.4. Emergency telephone number: +49 (0) 89 19240 (Giftnotruf Technische Universität München)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

This product has been treated with biocides for preservation.

Hazard statements

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.
P273 Avoid release to the environment.
P501 Dispose of waste according to applicable legislation.

Special labelling of certain mixtures



W9 2 in 1 Premium Glaze Wax

EUH066 Repeated exposure may cause skin dryness or cracking.
 EUH208 Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1)., 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
	aliphatic hydrocarbons, C11-C13, isoalkanes, <2% aromatics			25 - < 30 %
	920-901-0		01-2119456810-40	
	Asp. Tox. 1; H304 EUH066			
64-17-5	ethanol			5 - < 10 %
	200-578-6		01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
	hydrocarbons, C10-C12, isoalkanes, < 2% aromatics			1 - < 5 %
	923-037-2		01-2119471991-29	
	Flam. Liq. 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H304 H411 EUH066			
68439-50-9	alcohols, C12-C14, ethoxylated			< 1 %
	500-213-3		01-2119487984-16	
	Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 3; H318 H400 H412			
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).			< 0.1 %
	-	613-167-00-5		
	Acute Tox. 1, Acute Tox. 2, Acute Tox. 3, Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1 (M-Factor = 100), Aquatic Chronic 1 (M-Factor = 100); H310 H330 H301 H314 H318 H317 H400 H410 EUH071			
2682-20-4	2-methyl-2H-isothiazol-3-one			< 0.1 %
	220-239-6		01-2120764690-50	
	Acute Tox. 2, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1 (M-Factor = 10), Aquatic Chronic 1 (M-Factor = 1); H330 H311 H301 H314 H318 H317 H400 H410 EUH071			

Full text of H and EUH statements: see section 16.



W9 2 in 1 Premium Glaze Wax

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No special measures are necessary. When in doubt or if symptoms are observed, get medical advice.

After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off contaminated clothing and wash it before reuse.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a doctor.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Dry extinguishing powder. Carbon dioxide (CO₂). Water spray jet. Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Gases/vapours, irritant.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and



W9 2 in 1 Premium Glaze Wax

clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

No special measures are necessary. Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

Advice on protection against fire and explosion

No special fire protection measures are necessary. Only use the material in places where open light, fire and other flammable sources can be kept away.

Further information on handling

Take off contaminated clothing. Wash hands before breaks and after work. When using do not smoke. When using do not eat or drink. Avoid contact with skin, eyes and clothes. Avoid breathing dust/fume/gas/mist/vapours/spray.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed.

Hints on joint storage

Do not store together with: Oxidising agent. Strong acid. Strong alkali.

Further information on storage conditions

Recommended storage temperature: 15-25°C

7.3. Specific end use(s)

Automotive care products

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



W9 2 in 1 Premium Glaze Wax

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
1344-28-1	Aluminium oxides, respirable dust	-	4		TWA (8 h)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64-17-5	ethanol			
	Consumer DNEL, long-term	dermal	systemic	206 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	87 mg/kg bw/day
	Worker DNEL, acute	inhalation	local	1900 mg/m ³
	Worker DNEL, long-term	inhalation	systemic	950 mg/m ³
	Worker DNEL, long-term	dermal	systemic	343 mg/kg bw/day
	Consumer DNEL, acute	inhalation	local	950 mg/m ³
1344-28-1	aluminium oxide			
	Consumer DNEL, long-term	oral	systemic	3,29 mg/kg bw/day
	Worker DNEL, long-term	inhalation	local	15,63 mg/m ³
68439-50-9	alcohols, C12-C14, ethoxylated			
	Worker DNEL, long-term	inhalation	systemic	294 mg/m ³
	Worker DNEL, long-term	dermal	systemic	2080 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	25 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	87 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	1252 mg/kg bw/day
2682-20-4	2-methyl-2H-isothiazol-3-one			
	Worker DNEL, long-term	inhalation	local	0,021 mg/m ³
	Consumer DNEL, long-term	inhalation	local	0,012 mg/m ³
	Consumer DNEL, long-term	oral	systemic	0,027 mg/kg bw/day
	Worker DNEL, acute	inhalation	local	0,043 mg/m ³

W9 2 in 1 Premium Glaze Wax

PNEC values

CAS No	Substance	Value
Environmental compartment		
64-17-5	ethanol	
Freshwater		0,96 mg/l
Marine water		0,79 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		2,9 mg/kg
Micro-organisms in sewage treatment plants (STP)		580 mg/l
Soil		0,63 mg/kg
1344-28-1	aluminium oxide	
Freshwater		0,0749 mg/l
Micro-organisms in sewage treatment plants (STP)		20 mg/l
68439-50-9	alcohols, C12-C14, ethoxylated	
Freshwater		0,0437 mg/l
Marine water		0,0437 mg/l
Freshwater sediment		31 mg/kg
Marine sediment		31 mg/kg
Micro-organisms in sewage treatment plants (STP)		10000 mg/l
Soil		1 mg/kg
2682-20-4	2-methyl-2H-isothiazol-3-one	
Freshwater		0,00339 mg/l
Marine water		0,00339 mg/l
Soil		0,047 mg/kg

8.2. Exposure controls



Appropriate engineering controls

Use only in well-ventilated areas.

Protective and hygiene measures

Take off contaminated clothing. Wash hands before breaks and after work. When using do not smoke. When using do not eat or drink. Avoid contact with skin, eyes and clothes. Avoid breathing dust/fume/gas/mist/vapours/spray.



W9 2 in 1 Premium Glaze Wax

Eye/face protection

Wear eye protection/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves must be worn.

Recommended glove articles: HyFlex® Foam (EN 420, EN 388 (3131)).

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

No special environmental measures are necessary. Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Paste
Colour:	white
Odour:	characteristic

pH-Value (at 20 °C):	7,2
----------------------	-----

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	78 °C
Flash point:	36 °C DIN 51755
Sustaining combustion:	Not sustaining combustion

Flammability

Solid:	not determined
Gas:	not applicable
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	7 vol. %
Ignition temperature:	>200 °C

Auto-ignition temperature

Solid:	not determined
--------	----------------

Test method



W9 2 in 1 Premium Glaze Wax

Gas:	not applicable
Decomposition temperature:	not determined
Oxidizing properties	
Not oxidising.	
Vapour pressure: (at 20 °C)	0,4 hPa
Density (at 20 °C):	0,9 g/cm ³
Water solubility: (at 20 °C)	miscible
Solubility in other solvents	
not determined	
Partition coefficient:	not determined
Viscosity / dynamic: (at 20 °C)	5000-8000 mPa·s
Vapour density:	not determined
Evaporation rate:	not determined
Solvent content:	38,55 %
9.2. Other information	
Solid content:	not determined
Not sustaining combustion	

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Only use the material in places where open light, fire and other flammable sources can be kept away.

10.5. Incompatible materials

Oxidising agent. Strong acid. Strong alkali.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information



THE SCIENCE OF GLOSS

Page 9 of 18

Safety Data Sheet according to Regulation (EC) No 1907/2006

GB - EN

Revision date: 02.04.2020/Revision No:2,00

PDF Print date: 02.04.2020

W9 2 in 1 Premium Glaze Wax

11.1. Information on toxicological effects

Toxicokinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.



W9 2 in 1 Premium Glaze Wax

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	aliphatic hydrocarbons, C11-C13, isoalkanes, <2% aromatics				
	oral	LD50 >5000 mg/kg	Rat	ECHA	OECD 401
	dermal	LD50 >5000 mg/kg	Rat	ECHA	OECD 402
	inhalation (4 h) vapour	LC50 >2500 mg/l	Rat	ECHA	OECD 403
64-17-5	ethanol				
	oral	LD50 7060 mg/kg	Rat	GESTIS	
	dermal	LD50 >20000 mg/kg	Rabbit	literature value	
	inhalation (4 h) vapour	LC50 117-125 mg/l	Rat	ECHA	
	hydrocarbons, C10-C12, isoalkanes, < 2% aromatics				
	oral	LD50 >5000 mg/kg	Rat	ECHA	OECD TG 401
	dermal	LD50 >5000 mg/kg	Rabbit	ECHA	OECD TG 402
	inhalation vapour	LC50 >5000 mg/l	Rat	ECHA	OECD TG 403
68439-50-9	alcohols, C12-C14, ethoxylated				
	oral	LD50 >2000 mg/kg	Rat	ECHA	
	dermal	LD50 >2000 mg/kg	Rat	ECHA	
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).				
	oral	LD50 66 mg/kg	Rat	Thor	
	dermal	LD50 >141 mg/kg		Thor	
	inhalation vapour	ATE 0,5 mg/l			
	inhalation aerosol	ATE 0,05 mg/l			
2682-20-4	2-methyl-2H-isothiazol-3-one				
	oral	LD50 120 mg/kg	Ratte		
	dermal	LD50 242 mg/kg	Ratte		



W9 2 in 1 Premium Glaze Wax

	inhalation vapour	ATE	0,5 mg/l			
	inhalation aerosol	ATE	0,05 mg/l			

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1), 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



W9 2 in 1 Premium Glaze Wax

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
	aliphatic hydrocarbons, C11-C13, isoalkanes, <2% aromatics					
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	ECHA	
	Acute algae toxicity	ErC50 >1000 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA	
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h	Daphnia magna (Big water flea)	ECHA	
	Algae toxicity	NOEC 1000 mg/l	3 d	Pseudokirchneriella subcapitata		
64-17-5	ethanol					
	Acute fish toxicity	LC50 8140 mg/l	96 h	Leuciscus idus (golden orfe)	ECHA	
	Acute algae toxicity	ErC50 >100 mg/l	96 h	Chlorella pyrenoidosa	literature value	
	Acute crustacea toxicity	EC50 9268 - 14221 mg/l	48 h	Daphnia magna	IUCLID	
	hydrocarbons, C10-C12, isoalkanes, < 2% aromatics					
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	ECHA	
	Acute algae toxicity	ErC50 >1000 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA	
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h	Daphnia magna (Big water flea)	ECHA	
	Algae toxicity	NOEC 1000 mg/l	3 d	Pseudokirchneriella subcapitata		
	Crustacea toxicity	NOEC <1 mg/l	21 d	Daphnia magna (Big water flea)	ECHA	
68439-50-9	alcohols, C12-C14, ethoxylated					
	Acute fish toxicity	LC50 0,876 mg/l	96 h	Brachydanio rerio (zebra-fish)	ECHA	
	Acute algae toxicity	ErC50 0,41 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA	
	Acute crustacea toxicity	EC50 0,39 mg/l	48 h	Daphnia magna (Big water flea)	ECHA	
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).					
	Acute fish toxicity	LC50 0,22 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	Thor	OECD 203



W9 2 in 1 Premium Glaze Wax

	Acute algae toxicity	ErC50 mg/l	0,048	72 h	Pseudokirchneriella subcapitata	Thor	OECD 201
	Acute crustacea toxicity	EC50	0,1 mg/l	48 h	Daphnia magna (Big water flea)	Thor	OECD 202
	Fish toxicity	NOEC mg/l	0,098	28 d	Oncorhynchus mykiss (Rainbow trout)	Thor	OECD 210
	Algae toxicity	NOEC mg/l	0,0012	3 d	Pseudokirchneriella subcapitata	Thor	OECD 201
	Crustacea toxicity	NOEC mg/l	0,004	21 d	Daphnia magna (Big water flea)	Thor	OECD 211
	Acute bacteria toxicity	(7,92 mg/l)		3 h	Activated sludge		OECD 209
2682-20-4	2-methyl-2H-isothiazol-3-one						
	Acute fish toxicity	LC50 mg/l	4,77	96 h	Oncorhynchus mykiss (Rainbow trout)	ECHA	OECD 203
	Acute algae toxicity	ErC50 mg/l	0,103	72 h	Selenastrum capricornutum	ECHA	OECD 201
	Acute crustacea toxicity	EC50 mg/l	0,934	48 h	Daphnia magna (Big water flea)	ECHA	OECD 202
	Acute bacteria toxicity	(34,6 mg/l)		0 h		Thor	DIN 38412-3 (TTC-Test)

12.2. Persistence and degradability

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.



W9 2 in 1 Premium Glaze Wax

CAS No	Chemical name	Method	Value	d	Source
	aliphatic hydrocarbons, C11-C13, isoalkanes, <2% aromatics	OECD 301 F	31,3 %	28	ECHA
	Evidence for inherent biodegradability.				
64-17-5	ethanol	OECD 301 C	>89%	14	ECHA
	Readily biodegradable (according to OECD criteria).				
	hydrocarbons, C10-C12, isoalkanes, < 2% aromatics	OECD 301 F	31,3%	21	ECHA
	Evidence for inherent biodegradability.				
68439-50-9	alkohols, C12-C14, ethoxylated	BODIS-Test	92%	28	
	Readily biodegradable (according to OECD criteria).				
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).	OECD 301 A	>70 %	28	Thor
	Readily biodegradable (according to OECD criteria).				
		OECD 301 D	>60%		Thor
	Readily biodegradable (according to OECD criteria).				
		OECD 302 B	100%		Thor
	Readily biodegradable (according to OECD criteria).				
2682-20-4	2-methyl-2H-isothiazol-3-one	OECD 309	>70%	28	ECHA
	Readily biodegradable (according to OECD criteria).				

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol	-0,31
2682-20-4	2-methyl-2H-isothiazol-3-one	<0,32

**W9 2 in 1 Premium Glaze Wax****BCF**

CAS No	Chemical name	BCF	Species	Source
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).	3,6		EPIWIN, S 1177
2682-20-4	2-methyl-2H-isothiazol-3-one	3,16	calculated.	

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled.

SECTION 14: Transport information**Land transport (ADR/RID)**

- 14.1. UN number:** No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

- 14.1. UN number:** No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.



W9 2 in 1 Premium Glaze Wax

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.

14.4. Packing group: No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number: No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.

14.4. Packing group: No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.

14.4. Packing group: No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2010/75/EU (VOC): 35,604 % (320,434 g/l)

2004/42/EC (VOC): 35,658 % (320,923 g/l)

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.



W9 2 in 1 Premium Glaze Wax

Substance/product listed in the following inventories

EU / Schweiz	yes
Taiwan	unknown
New Zealand	unknown
Canada	yes
Australia	yes
Japan	unknown
China	unknown
Korea	unknown
Philippines	unknown

SECTION 16: Other information

Abbreviations and acronyms

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service
- LC50: Lethal concentration, 50%
- LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.

**W9 2 in 1 Premium Glaze Wax**

H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.
EUH208	Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1)., 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Formulation or re-packing	F	-	-	8a, 9	2	-	-	
2	Automotive care products, Industrial uses	IS	-	-	7, 10, 17	4	-	-	
3	Automotive care products, Professional uses	PW	-	-	10, 11, 17	8a	-	-	
4	Automotive care products, Consumer use	C	-	31	-	8a	-	-	

LCS: Life cycle stages

SU: Sectors of use

PC: Product categories

PROC: Process categories

ERC: Environmental release categories

AC: Article categories

TF: Technical functions

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)