



## E1200 Polishing Compound extra heavy cut

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

E1200 Polishing Compound extra heavy cut

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Automotive care products

#### 1.3. Details of the supplier of the safety data sheet

Company name:	SCHOLL Concepts GmbH	
	Polish & Pad Manufaktur	
Street:	Maybachstrasse 7	
Place:	D-71686 Remseck	
Telephone:	+49 (0) 7141 29299 - 0	Telefax: +49 (0) 7141 29299 - 10
e-mail:	sds@schollconcepts.com	
Internet:	www.schollconcepts.com	

**1.4. Emergency telephone number:** +49 (0) 89 19240 (Giftnotruf Technische Universität München)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Regulation (EC) No. 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No. 1272/2008.

#### 2.2. Label elements

##### Regulation (EC) No. 1272/2008

##### Hazard components for labelling

This product has been treated with biocides for preservation.

##### Precautionary statements

P102 Keep out of reach of children.

##### Special labelling of certain mixtures

EUH208	Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

**E1200 Polishing Compound extra heavy cut****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
57-55-6	propan-1,2-diol			< 0.1 %
	200-338-0		01-2119456809-23	

Full text of H and EUH statements: see section 16.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

No special measures are necessary. When in doubt or if symptoms are observed, get medical advice.

**After inhalation**

Provide fresh air. In case of respiratory tract irritation, consult a physician.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap. Take off contaminated clothing and wash it before reuse.

**After contact with eyes**

Rinse immediately carefully and thoroughly with eye-bath or water.

**After ingestion**

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Foam. Dry extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Water spray jet. Co-ordinate fire-fighting measures to the fire surroundings.

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

In case of fire may be liberated: Gases/vapours, irritant.



## E1200 Polishing Compound extra heavy cut

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

No special measures are necessary. Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

#### Advice on protection against fire and explosion

No special fire protection measures are necessary. Only use the material in places where open light, fire and other flammable sources can be kept away.

#### Further information on handling

Take off contaminated clothing. Wash hands before breaks and after work. When using do not smoke. When using do not eat or drink. Avoid contact with skin, eyes and clothes. Avoid breathing dust/fume/gas/mist/vapours/spray.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed.

#### Hints on joint storage

Do not store together with: Oxidising agent. Strong acid. Strong alkali.



**E1200 Polishing Compound extra heavy cut**

**Further information on storage conditions**

Recommended storage temperature: 15-25°C

**7.3. Specific end use(s)**

Automotive care products

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
1344-28-1	Aluminium oxides, respirable dust	-	4		TWA (8 h)	WEL
56-81-5	Glycerol, mist	-	10		TWA (8 h)	WEL
57-55-6	Propane-1,2-diol, particulates	-	10		TWA (8 h)	WEL

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
1344-28-1	aluminium oxide			
	Consumer DNEL, long-term	oral	systemic	3,29 mg/kg bw/day
	Worker DNEL, long-term	inhalation	local	15,63 mg/m <sup>3</sup>
56-81-5	glycerol			
	Consumer DNEL, long-term	oral	systemic	229 mg/kg bw/day
	Worker DNEL, long-term	inhalation	local	56 mg/m <sup>3</sup>
	Consumer DNEL, long-term	inhalation	local	33 mg/m <sup>3</sup>
57-55-6	propan-1,2-diol			
	Consumer DNEL, long-term	inhalation	local	10 mg/m <sup>3</sup>
	Worker DNEL, long-term	inhalation	systemic	168 mg/m <sup>3</sup>
	Worker DNEL, long-term	inhalation	local	10 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	213 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	50 mg/m <sup>3</sup>
	Consumer DNEL, long-term	oral	systemic	85 mg/kg bw/day

## E1200 Polishing Compound extra heavy cut

### PNEC values

CAS No	Substance	Value
Environmental compartment		
1344-28-1	aluminium oxide	
Freshwater		0,0749 mg/l
Micro-organisms in sewage treatment plants (STP)		20 mg/l
56-81-5	glycerol	
Freshwater		0,885 mg/l
Marine water		0,00885 mg/l
Freshwater sediment		3,3 mg/kg
Marine sediment		0,33 mg/kg
Soil		0,141 mg/kg
57-55-6	propan-1,2-diol	
Freshwater		260 mg/l
Marine water		26 mg/l
Freshwater sediment		572 mg/kg
Marine sediment		57,2 mg/kg
Micro-organisms in sewage treatment plants (STP)		20000 mg/l
Soil		50 mg/kg

### 8.2. Exposure controls



#### Appropriate engineering controls

Use only in well-ventilated areas.

#### Protective and hygiene measures

Take off contaminated clothing. Wash hands before breaks and after work. When using do not smoke. When using do not eat or drink. Avoid contact with skin, eyes and clothes. Avoid breathing dust/fume/gas/mist/vapours/spray.

#### Eye/face protection

Wear eye protection/face protection.

#### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the



## E1200 Polishing Compound extra heavy cut

specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves must be worn.

Recommended glove articles: HyFlex® Foam (EN 420, EN 388 (3131)).

### Skin protection

Wear suitable protective clothing.

### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

### Environmental exposure controls

No special environmental measures are necessary. Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Paste
Colour:	light green
Odour:	characteristic
pH-Value (at 20 °C):	7,8

#### Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	100 °C
Flash point:	130 °C

#### Flammability

Solid:	not determined
Gas:	not applicable
Lower explosion limits:	0,4 vol. %
Upper explosion limits:	0,5 vol. %
Ignition temperature:	>200 °C

#### Auto-ignition temperature

Solid:	not determined
Gas:	not applicable
Decomposition temperature:	not determined

#### Oxidizing properties

Not oxidising.	
Density (at 20 °C):	1,44 g/cm <sup>3</sup>



## E1200 Polishing Compound extra heavy cut

Water solubility: completely miscible  
(at 20 °C)

**Solubility in other solvents**  
not determined

Partition coefficient: not determined

Viscosity / dynamic: 55000-60000 mPa·s  
(at 20 °C)

Vapour density: not determined

Evaporation rate: not determined

Solvent content: 20,89 %

### 9.2. Other information

Solid content: not determined

Not sustaining combustion

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

### 10.4. Conditions to avoid

Only use the material in places where open light, fire and other flammable sources can be kept away.

### 10.5. Incompatible materials

Oxidising agent. Strong acid. Strong alkali.

### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Toxicokinetics, metabolism and distribution

No information available.

#### Acute toxicity

Based on available data, the classification criteria are not met.

**E1200 Polishing Compound extra heavy cut**

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
57-55-6	propan-1,2-diol				
	oral	LD50 >2001 mg/kg	Rat		
	dermal	LD50 >2001 mg/kg	Rabbit		

**Irritation and corrosivity**

Based on available data, the classification criteria are not met.

**Sensitising effects**

Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).. May produce an allergic reaction.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Additional information on tests**

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

**SECTION 12: Ecological information****12.1. Toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
57-55-6	propan-1,2-diol					
	Acute fish toxicity	LC50 40613 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	Env. Canada (1990)	
	Acute algae toxicity	ErC50 24200 mg/l	72 h	Pseudokirchnerella subcapitata	OECD 201	
	Acute crustacea toxicity	EC50 18340 mg/l	48 h	Ceriodaphnia dubia	EPA 600/4-90/0-27	

**12.2. Persistence and degradability**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.



**E1200 Polishing Compound extra heavy cut**

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
57-55-6	propan-1,2-diol			
	OECD Guideline 301 F	>70	28	

**12.3. Bioaccumulative potential**

The product has not been tested.

**12.4. Mobility in soil**

The product has not been tested.

**12.5. Results of PBT and vPvB assessment**

The product has not been tested.

**12.6. Other adverse effects**

No information available.

**Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

**Contaminated packaging**

Non-contaminated packages may be recycled.

**SECTION 14: Transport information****Land transport (ADR/RID)**

- 14.1. UN number:** No dangerous good in sense of this transport regulation.  
**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.  
**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.  
**14.4. Packing group:** No dangerous good in sense of this transport regulation.

**Inland waterways transport (ADN)**

- 14.1. UN number:** No dangerous good in sense of this transport regulation.  
**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.  
**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.  
**14.4. Packing group:** No dangerous good in sense of this transport regulation.

**Marine transport (IMDG)**

**E1200 Polishing Compound extra heavy cut**

- 14.1. UN number:** No dangerous good in sense of this transport regulation.  
**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.  
**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.  
**14.4. Packing group:** No dangerous good in sense of this transport regulation.

**Air transport (ICAO-TI/IATA-DGR)**

- 14.1. UN number:** No dangerous good in sense of this transport regulation.  
**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.  
**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.  
**14.4. Packing group:** No dangerous good in sense of this transport regulation.

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**14.6. Special precautions for user**

No dangerous good in sense of this transport regulation.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No dangerous good in sense of this transport regulation.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2010/75/EU (VOC): 0,002 % (0,022 g/l)  
2004/42/EC (VOC): 0,002 % (0,024 g/l)  
Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

**Additional information**

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).  
Water hazard class (D): 1 - slightly hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.



## E1200 Polishing Compound extra heavy cut

### Substance/product listed in the following inventories

EU / Schweiz	yes
Taiwan	yes
New Zealand	unknown
USA	yes
Canada	yes
Australia	yes
Japan	unknown
China	yes
Korea	yes
Philippines	unknown

## SECTION 16: Other information

### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road )  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%

### Relevant H and EUH statements (number and full text)

EUH208	Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



## E1200 Polishing Compound extra heavy cut

### Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Formulation or re-packing	F	-	-	8a, 9	2	-	-	
2	Automotive care products, Industrial uses	IS	-	-	7, 10, 17	4	-	-	
3	Automotive care products, Professional uses	PW	-	-	10, 11, 17	8a	-	-	
4	Automotive care products, Consumer use	C	-	31	-	8a	-	-	

LCS: Life cycle stages

SU: Sectors of use

PC: Product categories

PROC: Process categories

ERC: Environmental release categories

AC: Article categories

TF: Technical functions

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

© by SCHOLL Concepts GmbH