



## CF02 CLAY&FINISH Fluid

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

CF02 CLAY&FINISH Fluid

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Washing and cleaning products

#### 1.3. Details of the supplier of the safety data sheet

Company name:	SCHOLL Concepts GmbH	
	Polish & Pad Manufaktur	
Street:	Maybachstrasse 7	
Place:	D-71686 Remseck	
Telephone:	+49 (0) 7141 29299 - 0	Telefax: +49 (0) 7141 29299 - 10
e-mail:	sds@schollconcepts.com	
Internet:	www.schollconcepts.com	

1.4. Emergency telephone number: +49 (0) 89 19240 (Giftnotruf Technische Universität München)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Regulation (EC) Nr. 1272/2008.

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

#### 2.2. Label elements

##### Regulation (EC) Nr. 1272/2008.

##### Hazard components for labelling

This product has been treated with biocides for preservation.

##### Precautionary statements

P102 Keep out of reach of children.

##### Special labelling of certain mixtures

EUH208 Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients



**CF02 CLAY&FINISH Fluid**

**3.2. Mixtures**

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
67-63-0	isopropanol			1 - < 5 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
5131-66-8	3-Butoxy-2-propanol			1 - < 5 %
	225-878-4		01-2119475527-28	
	Skin Irrit. 2, Eye Irrit. 2; H315 H319			
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).			< 0.1 %
	611-341-5	613-167-00-5		
	Acute Tox. 2, Acute Tox. 2, Acute Tox. 3, Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H310 H301 H314 H318 H317 H400 H410 EUH071			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
67-63-0	200-661-7	isopropanol	1 - < 5 %
		inhalation: LC50 = >25 mg/l (vapours); dermal: LD50 = 12800 mg/kg; oral: LD50 = 5840 mg/kg	
5131-66-8	225-878-4	3-Butoxy-2-propanol	1 - < 5 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = 3300 mg/kg	
55965-84-9	611-341-5	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).	< 0.1 %
		inhalation: ATE = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: LD50 = >141 mg/kg; oral: LD50 = 66 mg/kg Skin Corr. 1C; H314: >= 0,6 - 100 Skin Irrit. 2; H315: >= 0,06 - < 0,6 Eye Dam. 1; H318: >= 0,6 - 100 Eye Irrit. 2; H319: >= 0,06 - < 0,6 Skin Sens. 1A; H317: >= 0,0015 - 100 M acute; H400: M=100 M chron.; H410: M=100	

**Labelling for contents according to Regulation (EC) No 648/2004**

< 5 % non-ionic surfactants, perfumes, preservation agents  
(Methylchloroisothiazolinone/Methylisothiazolinone).

**SECTION 4: First aid measures**



## CF02 CLAY&FINISH Fluid

### 4.1. Description of first aid measures

#### General information

No special measures are necessary. When in doubt or if symptoms are observed, get medical advice.

#### After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off contaminated clothing and wash it before reuse.

#### After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

#### After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Foam. Dry extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Water spray jet. Co-ordinate fire-fighting measures to the fire surroundings.

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

No special measures are necessary.

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General measures

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and



## CF02 CLAY&FINISH Fluid

clothes. Use personal protection equipment.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

### 6.3. Methods and material for containment and cleaning up

#### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Use only in well-ventilated areas. Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

#### Advice on protection against fire and explosion

No special fire protection measures are necessary. Only use the material in places where open light, fire and other flammable sources can be kept away.

#### Further information on handling

Take off contaminated clothing. Wash hands before breaks and after work. When using do not smoke. When using do not eat or drink. Avoid contact with skin, eyes and clothes. Avoid breathing dust/fume/gas/mist/vapours/spray.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed.

#### Hints on joint storage

Do not store together with: Oxidising agent. Strong acid. Strong alkali.

#### Further information on storage conditions

Recommended storage temperature: 15-25°C

### 7.3. Specific end use(s)

Automotive care products

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

**CF02 CLAY&FINISH Fluid****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
67-63-0	isopropanol			
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	89 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	systemic	500 mg/m <sup>3</sup>
5131-66-8	3-Butoxy-2-propanol			
Consumer DNEL, long-term		dermal	systemic	22 mg/kg bw/day
Consumer DMEL, long-term		oral	systemic	12,5 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	52 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	147 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	systemic	43 mg/m <sup>3</sup>

## CF02 CLAY&FINISH Fluid

### PNEC values

CAS No	Substance	
Environmental compartment		Value
67-63-0	isopropanol	
Freshwater		140,9 mg/kg
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Soil		28 mg/kg
5131-66-8	3-Butoxy-2-propanol	
Freshwater		0,525 mg/l
Marine water		0,0525 mg/l
Freshwater sediment		2,36 mg/kg
Marine sediment		0,236 mg/kg
Soil		0,16 mg/kg

### 8.2. Exposure controls



#### Appropriate engineering controls

Use only in well-ventilated areas.

#### Protective and hygiene measures

Take off contaminated clothing. Wash hands before breaks and after work. When using do not smoke. When using do not eat or drink. Avoid contact with skin, eyes and clothes. Avoid breathing dust/fume/gas/mist/vapours/spray.

#### Eye/face protection

Wear eye/face protection.

#### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves must be worn.

Recommended glove articles : Rotiprotect Nitril eco , Thickness of the glove material 0,10 mm, level 1 > 10

**CF02 CLAY&FINISH Fluid**

min. (DIN EN 374) Disposable gloves

**Skin protection**

Wear suitable protective clothing.

**Respiratory protection**

Warning! In case of inadequate ventilation wear respiratory protection.

**Environmental exposure controls**

No special environmental measures are necessary. Do not allow uncontrolled discharge of product into the environment.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour:	characteristic
pH-Value (at 20 °C):	6,0

**Changes in the physical state**

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	100 °C
Flash point:	>61 °C

**Flammability**

Solid/liquid:	not applicable
Gas:	not applicable
Lower explosion limits:	2 vol. %
Upper explosion limits:	12 vol. %
Auto-ignition temperature:	425 °C

**Self-ignition temperature**

Solid:	not applicable
Gas:	not applicable
Decomposition temperature:	not determined

**Oxidizing properties**

Not oxidising.

Vapour pressure: (at 20 °C)	48 hPa
Density (at 20 °C):	1 g/cm <sup>3</sup>



## CF02 CLAY&FINISH Fluid

Water solubility:	completely miscible
<b>Solubility in other solvents</b> not determined	
Partition coefficient n-octanol/water:	not determined
Viscosity / dynamic: (at 20 °C)	<7 mPa·s
Evaporation rate:	not determined
Solvent content:	3,95 %

### 9.2. Other information

Solid content:	not determined
----------------	----------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

### 10.4. Conditions to avoid

Only use the material in places where open light, fire and other flammable sources can be kept away.

### 10.5. Incompatible materials

Oxidising agent. Strong acid. Strong alkali.

### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in the Regulation (EC) Nr. 1272/2008

#### Toxicokinetics, metabolism and distribution

No information available.

#### Acute toxicity

Based on available data, the classification criteria are not met.



## CF02 CLAY&FINISH Fluid

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-63-0	isopropanol				
	oral	LD50 5840 mg/kg	Rat	ECHA	OECD 401
	dermal	LD50 12800 mg/kg	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50 >25 mg/l	Rat	ECHA	OECD 403
5131-66-8	3-Butoxy-2-propanol				
	oral	LD50 3300 mg/kg	Rat	ECHA	OECD 401
	dermal	LD50 >2000 mg/kg	Rat	GESTIS	OECD 401
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).				
	oral	LD50 66 mg/kg	Rat	Thor	
	dermal	LD50 >141 mg/kg		Thor	
	inhalation vapour	ATE 0,5 mg/l			
	inhalation aerosol	ATE 0,05 mg/l			

### Irritation and corrosivity

Based on available data, the classification criteria are not met.

### Sensitising effects

Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).. May produce an allergic reaction.

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### Aspiration hazard

Based on available data, the classification criteria are not met.

### Specific effects in experiment on an animal

No information available.

### Additional information on tests

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

## CF02 CLAY&FINISH Fluid

### SECTION 12: Ecological information

#### 12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
67-63-0	isopropanol					
	Acute fish toxicity	LC50 9640 mg/l	96 h	Pimephales promelas (fathead minnow)	ECHA	OECD 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 9714 mg/l	48 h	Daphnia magna (Big water flea)	ECHA	OECD 202
5131-66-8	3-Butoxy-2-propanol					
	Acute fish toxicity	LC50 >560-1060 mg/l	96 h	Poecilia reticulata (Guppy)	ECHA	OECD 203
	Acute algae toxicity	ErC50 >1000 mg/l	96 h	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h	Daphnia magna (Big water flea)	ECHA	OECD 202
	Algae toxicity	NOEC 560 mg/l	4 d	Pseudokirchneriella subcapitata		
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).					
	Acute fish toxicity	LC50 0,22 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	Thor	OECD 203
	Acute algae toxicity	ErC50 0,048 mg/l	72 h	Pseudokirchneriella subcapitata	Thor	OECD 201
	Acute crustacea toxicity	EC50 0,1 mg/l	48 h	Daphnia magna (Big water flea)	Thor	OECD 202
	Fish toxicity	NOEC 0,098 mg/l	28 d	Oncorhynchus mykiss (Rainbow trout)	Thor	OECD 210
	Algae toxicity	NOEC 0,0012 mg/l	3 d	Pseudokirchneriella subcapitata	Thor	OECD 201
	Crustacea toxicity	NOEC 0,004 mg/l	21 d	Daphnia magna (Big water flea)	Thor	OECD 211
	Acute bacteria toxicity	(7,92 mg/l)	3 h	Activated sludge		OECD 209

#### 12.2. Persistence and degradability

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**CF02 CLAY&FINISH Fluid**

CAS No	Chemical name	Method	Value	d	Source
		Evaluation			
67-63-0	isopropanol	EU Method C.5	53%	5	ECHA
	Readily biodegradable (according to OECD criteria).				
5131-66-8	3-Butoxy-2-propanol	OECD 301 E	90%	28	ECHA
	Readily biodegradable (according to OECD criteria).				
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).				
	OECD 301 A	>70 %	28	Thor	
	Readily biodegradable (according to OECD criteria).				
	OECD 301 D	>60%		Thor	
	Readily biodegradable (according to OECD criteria).				

**12.3. Bioaccumulative potential**

The product has not been tested.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
67-63-0	isopropanol	0,05
5131-66-8	3-Butoxy-2-propanol	<3

**BCF**

CAS No	Chemical name	BCF	Species	Source
5131-66-8	3-Butoxy-2-propanol	<100		
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).	3,16		EPIWIN, S 1177

**12.4. Mobility in soil**

The product has not been tested.

**12.5. Results of PBT and vPvB assessment**

The product has not been tested.

**12.7. Other adverse effects**

No information available.



## CF02 CLAY&FINISH Fluid

### Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

#### Contaminated packaging

Non-contaminated packages may be recycled.

## SECTION 14: Transport information

### Land transport (ADR/RID)

- |                                   |  |
|-----------------------------------|--|
| 14.1. UN number:                  | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name:    | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group:              | No dangerous good in sense of this transport regulation. |

### Inland waterways transport (ADN)

- |                                   |  |
|-----------------------------------|--|
| 14.1. UN number:                  | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name:    | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group:              | No dangerous good in sense of this transport regulation. |

### Marine transport (IMDG)

- |                                   |  |
|-----------------------------------|--|
| 14.1. UN number:                  | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name:    | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group:              | No dangerous good in sense of this transport regulation. |

### Air transport (ICAO-TI/IATA-DGR)

- |                                   |  |
|-----------------------------------|--|
| 14.1. UN number:                  | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name:    | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group:              | No dangerous good in sense of this transport regulation. |

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

**CF02 CLAY&FINISH Fluid****14.6. Special precautions for user**

No special measures are necessary.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2010/75/EU (VOC):	3,977 % (39,766 g/l)
2004/42/EC (VOC):	3,984 % (39,837 g/l)
Information according to 2012/18/EU (SEVESO III):	Not subject to 2012/18/EU (SEVESO III)

**Additional information**

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

**National regulatory information**

Water hazard class (D): 1 - slightly hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**Substance/product listed in the following inventories**

EU / Schweiz	yes
Taiwan	yes
New Zealand	yes
USA	yes
Canada	yes
Australia	yes
Japan	yes
China	yes
Korea	yes
Philippines	yes

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 8,15.

**Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route



## CF02 CLAY&FINISH Fluid

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH208	Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



## CF02 CLAY&FINISH Fluid

### Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Formulation or re-packing	F	-	-	8a, 9	2	-	-	
2	Automotive care products, Industrial uses	IS	-	-	7, 10, 17	4	-	-	
3	Automotive care products, Professional uses	PW	-	-	10, 11, 17	8a	-	-	
4	Automotive care products, Consumer use	C	-	31	-	8a	-	-	

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

© by SCHOLL Concepts GmbH