



RAPID Plus Engine & Chassis Cleaner

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

RAPID Plus Engine & Chassis Cleaner

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Washing and cleaning products

1.3. Details of the supplier of the safety data sheet

Company name:	SCHOLL Concepts GmbH	
	Polish & Pad Manufaktur	
Street:	Maybachstrasse 7	
Place:	D-71686 Remseck	
Telephone:	+49 (0) 7141 29299 - 0	Telefax: +49 (0) 7141 29299 - 10
e-mail:	sds@schollconcepts.com	
Internet:	www.schollconcepts.com	

1.4. Emergency telephone number: +49 (0) 89 19240 (Giftnotruf Technische Universität München)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) Nr. 1272/2008.

Hazard categories:

Skin corrosion/irritation: Skin Corr. 1

Serious eye damage/eye irritation: Eye Dam. 1

Hazard Statements:

Causes severe skin burns and eye damage.

Causes serious eye damage.

2.2. Label elements

Regulation (EC) Nr. 1272/2008.

Hazard components for labelling

tetrasodium ethylene diamine tetraacetate

disodium metasilicate

Cocamidopropyl betaine

Sodium hydroxide

Signal word: Danger

RAPID Plus Engine & Chassis Cleaner

Pictograms:



Hazard statements

H314 Causes severe skin burns and eye damage.

Precautionary statements

P102 Keep out of reach of children.
P264 Wash hands thoroughly after handling.
P280 Wear protective gloves and eye/face protection.
P271 Use only outdoors or in a well-ventilated area.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P315 Get immediate medical advice/attention.
P302+P352 IF ON SKIN: Wash with plenty of water.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P501 Dispose of waste according to applicable legislation.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures



RAPID Plus Engine & Chassis Cleaner

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64-02-8	tetrasodium ethylene diamine tetraacetate			5 - < 10 %
	200-573-9	607-428-00-2	01-2119486762-27	
	Acute Tox. 4, Eye Dam. 1; H302 H318			
6834-92-0	disodium metasilicate			1 - < 5 %
	229-912-9	014-010-00-8	01-2119449811-37	
	Met. Corr. 1, Skin Corr. 1B, STOT SE 3; H290 H314 H335			
147170-44-3	Cocamidopropyl betaine			1 - < 5 %
	931-333-8		01-2119489410-39	
	Eye Dam. 1, Aquatic Chronic 3; H318 H412			
68515-73-1	Octyldecyl Glucoside			1 - < 5 %
	500-220-1		01-2119488530-36	
	Eye Dam. 1; H318			
1310-73-2	Sodium hydroxide			< 1 %
	215-185-5		01-2119457892-27	
	Met. Corr. 1, Skin Corr. 1A; H290 H314			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64-02-8	200-573-9	tetrasodium ethylene diamine tetraacetate	5 - < 10 %
	oral: LD50 = 1780-2000 mg/kg		
6834-92-0	229-912-9	disodium metasilicate	1 - < 5 %
	inhalation: LC50 = >2,06 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = 1372 mg/kg		
147170-44-3	931-333-8	Cocamidopropyl betaine	1 - < 5 %
	dermal: LD50 = >2000 mg/kg; oral: LD50 = 2335 mg/kg		
68515-73-1	500-220-1	Octyldecyl Glucoside	1 - < 5 %
	dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg		
1310-73-2	215-185-5	Sodium hydroxide	< 1 %
	dermal: LD50 = 1350 mg/kg; oral: LD50 = >191 mg/kg Skin Corr. 1A; H314: >= 5 - 100 Skin Irrit. 2; H315: >= 0,5 - < 5 Eye Irrit. 2; H319: >= 0,5 - < 5		



RAPID Plus Engine & Chassis Cleaner

Labelling for contents according to Regulation (EC) No 648/2004

5 % - < 15 % EDTA and salts thereof, < 5 % amphoteric surfactants, < 5 % non-ionic surfactants.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

IF exposed or concerned: Call a doctor. When in doubt or if symptoms are observed, get medical advice.
Remove contaminated, saturated clothing immediately.

After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Dry extinguishing powder. Carbon dioxide (CO₂). Water spray jet. Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Gases/vapours, corrosive

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists



RAPID Plus Engine & Chassis Cleaner

with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Wash hands before breaks and after work. When using do not smoke. When using do not eat or drink. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

No special fire protection measures are necessary. Only use the material in places where open light, fire and other flammable sources can be kept away.

Further information on handling

Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations.

Hints on joint storage

Do not store together with: Oxidising agent. Strong acid. Strong alkali.



RAPID Plus Engine & Chassis Cleaner

Further information on storage conditions

Recommended storage temperature: 15-25°C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
1310-73-2	Sodium hydroxide	-	2		STEL (15 min)	WEL

RAPID Plus Engine & Chassis Cleaner

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64-02-8	tetrasodium ethylene diamine tetraacetate			
Worker DNEL, long-term		inhalation	local	1,5 mg/m ³
Worker DNEL, acute		inhalation	local	3 mg/m ³
Consumer DNEL, long-term		inhalation	local	0,6 mg/m ³
Consumer DNEL, acute		inhalation	local	1,2 mg/m ³
Consumer DNEL, long-term		oral	systemic	25 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	3 mg/m ³
6834-92-0	disodium metasilicate			
Worker DNEL, long-term		inhalation	systemic	6,22 mg/m ³
Worker DNEL, long-term		dermal	systemic	1,49 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	1,55 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,74 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day
147170-44-3	Cocamidopropyl betaine			
Worker DNEL, long-term		inhalation	systemic	44 mg/m ³
Worker DNEL, long-term		dermal	systemic	12,5 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	13,04 mg/m ³
Consumer DNEL, long-term		dermal	systemic	7,5 mg/kg bw/day
68515-73-1	Octyldecyl Glucoside			
Worker DNEL, long-term		dermal	systemic	595000 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	420 mg/m ³
Consumer DNEL, long-term		dermal	systemic	357000 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	35,7 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	124 mg/m ³
1310-73-2	Sodium hydroxide			

RAPID Plus Engine & Chassis Cleaner

Worker DNEL, long-term	inhalation	local	1 mg/m ³
Consumer DNEL, long-term	inhalation	local	1 mg/m ³

PNEC values

CAS No	Substance	Value
Environmental compartment		
64-02-8	tetrasodium ethylene diamine tetraacetate	
Freshwater		2,83 mg/l
Marine water		0,283 mg/l
Micro-organisms in sewage treatment plants (STP)		50 mg/l
Soil		1,1 mg/kg
6834-92-0	disodium metasilicate	
Freshwater		7,5 mg/l
Marine water		1 mg/l
147170-44-3	Cocamidopropyl betaine	
Freshwater		0,013 mg/l
Marine water		0,0013 mg/l
Freshwater sediment		14,8 mg/kg
Marine sediment		1,48 mg/kg
Soil		0,8 mg/kg
68515-73-1	Octyldecyl Glucoside	
Freshwater		0,176 mg/l
Marine water		0,0176 mg/l
Freshwater sediment		1,516 mg/kg
Marine sediment		0,152 mg/kg
Secondary poisoning		111,11 mg/kg
Micro-organisms in sewage treatment plants (STP)		560 mg/l
Soil		0,654 mg/kg

8.2. Exposure controls





RAPID Plus Engine & Chassis Cleaner

Appropriate engineering controls

Use only in well-ventilated areas. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Wear protective gloves/protective clothing. Remove contaminated, saturated clothing immediately. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. When using do not smoke. Avoid contact with skin, eyes and clothes. Avoid breathing dust/fume/gas/mist/vapours/spray.

Eye/face protection

Wear eye/face protection. Suitable eye protection: Eye glasses with side protection (DIN EN 166)

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Recommended glove articles : Dermatril P 743, Thickness of the glove material 0,2 mm, level 2 >= 30 min. (DIN EN 374)

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

No special environmental measures are necessary. Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	blue
Odour:	characteristic
pH-Value (at 20 °C):	12,5

Changes in the physical state

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	100 °C
Flash point:	not determined



RAPID Plus Engine & Chassis Cleaner

Flammability

Solid/liquid:

not applicable

Gas:

not applicable

Lower explosion limits:

not determined

Upper explosion limits:

not determined

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Decomposition temperature:

not determined

Oxidizing properties

Not oxidising.

Vapour pressure:

not determined

(at 20 °C)

Vapour pressure:

not determined

(at 50 °C)

Density:

1,085 g/cm³

Water solubility:

easily soluble

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

not determined

Viscosity / dynamic:

not determined

(at 20 °C)

Relative vapour density:

not determined

Evaporation rate:

not determined

Solvent content:

not determined

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.



THE SCIENCE OF GLOSS

Page 11 of 19

Safety Data Sheet according to Regulation (EC) Nr. 1272/2008.

Revision date: 19.08.2021/Revision No:2,03

PDF Print date: 19.08.2021

RAPID Plus Engine & Chassis Cleaner

10.4. Conditions to avoid

Frost

10.5. Incompatible materials

Strong acid. Strong alkali. Oxidising agent.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in the Regulation (EC) Nr. 1272/2008

Toxicokinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

**RAPID Plus Engine & Chassis Cleaner**

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-02-8	tetrasodium ethylene diamine tetraacetate				
	oral	LD50 1780-2000 mg/kg	Rat	ECHA	OECD 401
6834-92-0	disodium metasilicate				
	oral	LD50 1372 mg/kg	Mouse	ECHA	
	dermal	LD50 >5000 mg/kg	Rat	ECHA	EPA OPPTS 870.1200
	inhalation (4 h) vapour	LC50 >2,06 mg/l	Rat	ECHA	EPA OPPTS 870.1300
147170-44-3	Cocamidopropyl betaine				
	oral	LD50 2335 mg/kg	Rat	ECHA	OECD 401
	dermal	LD50 >2000 mg/kg	Rat	ECHA	OECD 402
68515-73-1	Octyldecyl Glucoside				
	oral	LD50 >2000 mg/kg	Rat	ECHA	OECD 423
	dermal	LD50 >2000 mg/kg	Rabbit	ECHA	OECD 402
1310-73-2	Sodium hydroxide				
	oral	LD50 >191 mg/kg	Rat		
	dermal	LD50 1350 mg/kg	Rabbit		

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.



THE SCIENCE OF GLOSS

Page 13 of 19

Safety Data Sheet according to Regulation (EC) Nr. 1272/2008.

Revision date: 19.08.2021/Revision No:2,03

PDF Print date: 19.08.2021

RAPID Plus Engine & Chassis Cleaner

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.



RAPID Plus Engine & Chassis Cleaner

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64-02-8	tetrasodium ethylene diamine tetraacetate					
	Acute fish toxicity	LC50 >100 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	ECHA	OECD 203
	Acute algae toxicity	ErC50 >100 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Acute crustacea toxicity	EC50 >100 mg/l	48 h	Daphnia magna (Big water flea)	ECHA	DIN 38412, part 11
	Fish toxicity	NOEC >35,1 mg/l	35 d	Danio rerio (zebrafish)	ECHA	OECD 210
	Algae toxicity	NOEC 48,4 mg/l	3 d	Pseudokirchneriella subcapitata	ECHA	OECD 201
6834-92-0	disodium metasilicate					
	Acute fish toxicity	LC50 210 mg/l	96 h	Danio rerio (zebrafish)	ECHA	OECD 203
	Acute algae toxicity	ErC50 207 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Acute crustacea toxicity	EC50 1700 mg/l	48 h	Daphnia magna (Big water flea)	ECHA	EU Method C.2
147170-44-3	Cocamidopropyl betaine					
	Acute fish toxicity	LC50 1,1 mg/l	96 h	Danio rerio (zebrafish)	ECHA	OECD 203
	Acute algae toxicity	ErC50 1,5 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Acute crustacea toxicity	EC50 1,9 mg/l	48 h	Daphnia magna (Big water flea)	ECHA	OECD 202
	Fish toxicity	NOEC 1,1 mg/l	4 d	Danio rerio (zebrafish)	ECHA	OECD 203
	Algae toxicity	NOEC 0,3 mg/l	3 d	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Crustacea toxicity	NOEC 7 mg/l	2 d	Daphnia magna (Big water flea)	ECHA	OECD 202
68515-73-1	Octyldecyl Glucoside					
	Acute fish toxicity	LC50 170 mg/l	96 h	Danio rerio (zebrafish)	ECHA	ISO 7346/1-3
	Acute algae toxicity	ErC50 27,22 mg/l	72 h	Scenedesmus subspicatus	ECHA	(DIN 38412, part 9)
	Acute crustacea toxicity	EC50 >100 mg/l	48 h	Daphnia magna (Big water flea)	ECHA	OECD 202
1310-73-2	Sodium hydroxide					
	Acute fish toxicity	LC50 45,4 mg/l	96 h	Onchorhynchus mykiss		

**RAPID Plus Engine & Chassis Cleaner**

	Acute crustacea toxicity	EC50 mg/l	30-100	48 h	Saltwater Shrimp	ECHA	
--	--------------------------	--------------	--------	------	------------------	------	--

12.2. Persistence and degradability

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The surfactants contained in this mixture comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

CAS No	Chemical name	Method	Value	d	Source
		Evaluation			
64-02-8	tetrasodium ethylene diamine tetraacetate	OECD 301D	2%	28	ECHA
	Poorly biodegradable. Not readily biodegradable (according to OECD criteria)				
147170-44-3	Cocamidopropyl betaine	OECD 301B	91,6%	28	ECHA
	Readily biodegradable (according to OECD criteria).				
68515-73-1	Octyldecyl Glucoside	OECD 301E	100%	28	
	Readily biodegradable (according to OECD criteria).				

12.3. Bioaccumulative potential

The product has not been tested.

BCF

CAS No	Chemical name	BCF	Species	Source
147170-44-3	Cocamidopropyl betaine	<71		

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

RAPID Plus Engine & Chassis Cleaner

Disposal recommendations

This material and its container must be disposed of as hazardous waste. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	UN 1719
14.2. UN proper shipping name:	CAUSTIC ALKALI LIQUID, N.O.S. (SODIUM HYDROXIDE, SOLID)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8



Classification code:	C5
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

14.1. UN number:	UN 1719
14.2. UN proper shipping name:	CAUSTIC ALKALI LIQUID, N.O.S. (SODIUM HYDROXIDE, SOLID)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8



Classification code:	C5
Special Provisions:	274
Limited quantity:	5 L

RAPID Plus Engine & Chassis Cleaner

Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 1719
 14.2. UN proper shipping name: CAUSTIC ALKALI LIQUID, N.O.S. (SODIUM HYDROXIDE, SOLID)
 14.3. Transport hazard class(es): 8
 14.4. Packing group: III
 Hazard label: 8



Special Provisions: 223, 274
 Limited quantity: 5 L
 Excepted quantity: E1
 EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1719
 14.2. UN proper shipping name: CAUSTIC ALKALI LIQUID, N.O.S. (SODIUM HYDROXIDE, SOLID)
 14.3. Transport hazard class(es): 8
 14.4. Packing group: III
 Hazard label: 8



Special Provisions: A3 A803
 Limited quantity Passenger: 1 L
 Passenger LQ: Y841
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 852
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 856
 IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture



RAPID Plus Engine & Chassis Cleaner

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC
Regulation (EC) No. 648/2004 (Detergents regulation)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

Substance/product listed in the following inventories

EU / Schweiz	yes
Taiwan	no
New Zealand	yes
USA	yes
Canada	yes
Australia	yes
Japan	yes
China	yes
Korea	no
Philippines	yes

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,9,15.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

**RAPID Plus Engine & Chassis Cleaner**

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Corr. 1; H314	On basis of test data
Eye Dam. 1; H318	On basis of test data

Relevant H and EUH statements (number and full text)

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Industrial use of vehicle cleaning products	IS	-	-	7, 10, 17	4	-	-	
2	Formulation or re-packing	F	-	-	8a, 9	2	-	-	
3	Professional use of vehicle cleaning products	PW	-	-	10, 11, 17	8a	-	-	
4	Consumer use of washing and cleaning products	C	-	35	-	8a	-	-	

LCS: Life cycle stages

SU: Sectors of use

PC: Product categories

PROC: Process categories

ERC: Environmental release categories

AC: Article categories

TF: Technical functions

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

© by SCHOLL Concepts GmbH