



SW20 Premium Speed Wax

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

SW20 Premium Speed Wax

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Automotive care products

1.3. Details of the supplier of the safety data sheet

Company name:	SCHOLL Concepts GmbH	
	Polish & Pad Manufaktur	
Street:	Maybachstrasse 7	
Place:	D-71686 Remseck	
Telephone:	+49 (0) 7141 29299 - 0	Telefax: +49 (0) 7141 29299 - 10
e-mail:	sds@schollconcepts.com	
Internet:	www.schollconcepts.com	

1.4. Emergency telephone number: +49 (0) 89 19240 (Giftnotruf Technische Universität München)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) Nr. 1272/2008.

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

2.2. Label elements

Regulation (EC) Nr. 1272/2008.

Hazard components for labelling

This product has been treated with biocides for preservation.

Precautionary statements

P102 Keep out of reach of children.

Special labelling of certain mixtures

EUH208 Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

**SW20 Premium Speed Wax****3.2. Mixtures****Hazardous components**

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
111-76-2	2-butoxyethanol			1 - < 5 %
	203-905-0	603-014-00-0	01-2119475108-36	
	Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H332 H302 H315 H319			
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).			< 0.1 %
	611-341-5	613-167-00-5		
	Acute Tox. 2, Acute Tox. 2, Acute Tox. 3, Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H310 H301 H314 H318 H317 H400 H410 EUH071			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
111-76-2	203-905-0	2-butoxyethanol	1 - < 5 %
	inhalation: LC50 = 2,25 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = >2000 mg/kg; oral: ATE 1200 mg/kg		
55965-84-9	611-341-5	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).	< 0.1 %
	inhalation: ATE = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: LD50 = >141 mg/kg; oral: LD50 = 66 mg/kg Skin Corr. 1C; H314: >= 0,6 - 100 Skin Irrit. 2; H315: >= 0,06 - < 0,6 Eye Dam. 1; H318: >= 0,6 - 100 Eye Irrit. 2; H319: >= 0,06 - < 0,6 Skin Sens. 1A; H317: >= 0,0015 - 100 M acute; H400: M=100 M chron.; H410: M=100		

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

No special measures are necessary. When in doubt or if symptoms are observed, get medical advice.

After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off contaminated clothing and



SW20 Premium Speed Wax

wash it before reuse.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a doctor.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Dry extinguishing powder. Carbon dioxide (CO₂). Water spray jet. Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

No special measures are necessary.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.



SW20 Premium Speed Wax

6.4. Reference to other sections

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

Advice on protection against fire and explosion

No special fire protection measures are necessary. Only use the material in places where open light, fire and other flammable sources can be kept away.

Further information on handling

Take off contaminated clothing. Wash hands before breaks and after work. When using do not smoke. When using do not eat or drink. Avoid contact with skin, eyes and clothes. Avoid breathing dust/fume/gas/mist/vapours/spray.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed.

Hints on joint storage

Do not store together with: Oxidising agent. Strong acid. Strong alkali.

Further information on storage conditions

Recommended storage temperature: 15-25°C

7.3. Specific end use(s)

Automotive care products

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
111-76-2	2-Butoxyethanol	25	123		TWA (8 h)	WEL
		50	246		STEL (15 min)	WEL



SW20 Premium Speed Wax

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
111-76-2	2-Butoxyethanol	butoxyacetic acid (creatinine)	240 mmol/mol	urine	Post shift

DNEL/DMEL values

CAS No	Substance	DNEL type	Exposure route	Effect	Value
111-76-2	2-butoxyethanol				
		Worker DNEL, acute	inhalation	systemic	1091 mg/m ³
		Consumer DNEL, long-term	inhalation	systemic	59 mg/m ³
		Consumer DNEL, acute	inhalation	local	147 mg/m ³
		Consumer DNEL, long-term	oral	systemic	6,3 mg/kg bw/day
		Worker DNEL, long-term	inhalation	systemic	98 mg/m ³
		Worker DNEL, long-term	inhalation	local	246 mg/m ³
		Consumer DNEL, acute	inhalation	systemic	426 mg/m ³
		Consumer DNEL, acute	oral	systemic	26,7 mg/kg bw/day

PNEC values

CAS No	Substance	Environmental compartment	Value
111-76-2	2-butoxyethanol		
		Freshwater	8,8 mg/l
		Marine water	0,88 mg/l
		Freshwater sediment	34,6 mg/kg
		Marine sediment	3,46 mg/kg
		Secondary poisoning	0,02 mg/kg
		Micro-organisms in sewage treatment plants (STP)	463 mg/l
		Soil	2,33 mg/kg

8.2. Exposure controls

SW20 Premium Speed Wax



Appropriate engineering controls

Use only in well-ventilated areas.

Protective and hygiene measures

Take off contaminated clothing. Wash hands before breaks and after work. When using do not smoke. When using do not eat or drink. Avoid contact with skin, eyes and clothes. Avoid breathing dust/fume/gas/mist/vapours/spray.

Eye/face protection

Wear eye/face protection. Suitable eye protection: Eye glasses with side protection (DIN EN 166)

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves must be worn.

Recommended glove articles : Rotiprotect Nitril eco , Thickness of the glove material 0,10 mm, level 1 > 10 min. (DIN EN 374) Disposable gloves

Skin protection

Wear suitable protective clothing.

Respiratory protection

Warning! In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

No special environmental measures are necessary. Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	red
Odour:	characteristic
pH-Value (at 20 °C):	2,5
Changes in the physical state	
Melting point/freezing point:	not determined

**SW20 Premium Speed Wax**

Boiling point or initial boiling point and boiling range:	100 °C
Flash point:	>61 °C
Flammability	
Solid/liquid:	not applicable
Gas:	not applicable
Lower explosion limits:	not applicable
Upper explosion limits:	not applicable
Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Decomposition temperature:	not determined
Oxidizing properties	
Not oxidising.	
Vapour pressure:	1,4 hPa
Density (at 20 °C):	1 g/cm ³
Water solubility:	completely miscible
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined
Viscosity / dynamic: (at 20 °C)	3-15 mPa·s
Evaporation rate:	not determined
Solvent content:	2,52 %
9.2. Other information	
Solid content:	not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

SW20 Premium Speed Wax

10.4. Conditions to avoid

Only use the material in places where open light, fire and other flammable sources can be kept away.

10.5. Incompatible materials

Oxidising agent. Strong acid. Strong alkali.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in the Regulation (EC) Nr. 1272/2008

Toxicocinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
111-76-2	2-butoxyethanol				
	oral	ATE 1200 mg/kg			
	dermal	LD50 >2000 mg/kg	Guinea pig	ECHA	OECD 402
	inhalation (4 h) vapour	LC50 2,25 mg/l	Rat	ECHA	OECD 433
	inhalation aerosol	ATE 1,5 mg/l			
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).				
	oral	LD50 66 mg/kg	Rat	Thor	
	dermal	LD50 >141 mg/kg		Thor	
	inhalation vapour	ATE 0,5 mg/l			
	inhalation aerosol	ATE 0,05 mg/l			

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.



SW20 Premium Speed Wax

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

Additional information on tests

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
111-76-2	2-butoxyethanol					
	Acute fish toxicity	LC50 mg/l	1474	96 h	Oncorhynchus mykiss (Rainbow trout)	ECHA OECD 203
	Acute algae toxicity	ErC50 mg/l	720 mg/l	96 h	Pseudokirchneriella subcapitata	ECHA OECD 201
	Acute crustacea toxicity	EC50 mg/l	1800	48 h	Daphnia magna (Big water flea)	ECHA OECD 202
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).					
	Acute fish toxicity	LC50 mg/l	0,22	96 h	Oncorhynchus mykiss (Rainbow trout)	Thor OECD 203
	Acute algae toxicity	ErC50 mg/l	0,048	72 h	Pseudokirchneriella subcapitata	Thor OECD 201
	Acute crustacea toxicity	EC50 mg/l	0,1 mg/l	48 h	Daphnia magna (Big water flea)	Thor OECD 202
	Fish toxicity	NOEC mg/l	0,098	28 d	Oncorhynchus mykiss (Rainbow trout)	Thor OECD 210
	Algae toxicity	NOEC mg/l	0,0012	3 d	Pseudokirchneriella subcapitata	Thor OECD 201
	Crustacea toxicity	NOEC mg/l	0,004	21 d	Daphnia magna (Big water flea)	Thor OECD 211
	Acute bacteria toxicity	(7,92 mg/l)		3 h	Activated sludge	OECD 209

SW20 Premium Speed Wax

12.2. Persistence and degradability

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
111-76-2	2-butoxyethanol			
	OECD 301B	90,4%	28	ECHA
	Readily biodegradable (according to OECD criteria).			
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).			
	OECD 301 A	>70 %	28	Thor
	Readily biodegradable (according to OECD criteria).			
	OECD 301 D	>60%		Thor
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
111-76-2	2-butoxyethanol	0,81

BCF

CAS No	Chemical name	BCF	Species	Source
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).	3,16		EPIWIN, S 1177

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations



SW20 Premium Speed Wax

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

- | | |
|-----------------------------------|--|
| 14.1. UN number: | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

Inland waterways transport (ADN)

- | | |
|-----------------------------------|--|
| 14.1. UN number: | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

Marine transport (IMDG)

- | | |
|-----------------------------------|--|
| 14.1. UN number: | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

Air transport (ICAO-TI/IATA-DGR)

- | | |
|-----------------------------------|--|
| 14.1. UN number: | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No special measures are necessary.

14.7. Maritime transport in bulk according to IMO instruments

not applicable



SW20 Premium Speed Wax

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2010/75/EU (VOC):	2,556 % (25,56 g/l)
2004/42/EC (VOC):	2,578 % (25,781 g/l)

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

Substance/product listed in the following inventories

EU / Schweiz	yes
Taiwan	unknown
New Zealand	unknown
USA	yes
Canada	yes
Australia	yes
Japan	yes
China	yes
Korea	yes
Philippines	yes

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,6,7,9,15.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

**SW20 Premium Speed Wax**

CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH208	Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1).. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Formulation or re-packing	F	-	-	8a, 9	2	-	-	
2	Automotive care products, Industrial uses	IS	-	-	7, 10, 17	4	-	-	
3	Automotive care products, Professional uses	PW	-	-	10, 11, 17	8a	-	-	
4	Automotive care products, Consumer use	C	-	31	-	8a	-	-	

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories



THE SCIENCE OF GLOSS

Page 14 of 14

Safety Data Sheet according to Regulation (EC) Nr. 1272/2008.

Revision date: 15.07.2021/Revision No:2,01

PDF Print date: 15.07.2021

SW20 Premium Speed Wax

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

© by SCHOLL Concepts GmbH